

PRESERVATIVE PAINT CO -- OIL STAIN-DARK REDWOOD -- 8010-00-926-9129

===== Product Identification =====

Product ID:OIL STAIN-DARK REDWOOD

MSDS Date:01/01/1985

FSC:8010

NIIN:00-926-9129

MSDS Number: BFWYF

=== Responsible Party ===

Company Name:PRESERVATIVE PAINT CO

Address:5410 AIRPORT WAY S

Box:80387

City:SEATTLE

State:WA

ZIP:98108-1726

Country:US

CAGE:86589

=== Contractor Identification ===

Company Name:PRESERVATIVE PAINT CO

Address:5410 AIRPORT WAY S

Box:8038

7

City:SEATTLE

State:WA

ZIP:98108-1726

Country:US

CAGE:86589

===== Composition/Information on Ingredients =====

Ingred Name:PENTACHLOROPHENOL (SARA III)

CAS:87-86-5

RTECS #:SM6300000

Fraction by Wt: 4.04%

OSHA PEL:S, 0.5 MG/M3

ACGIH TLV:S, 0.5 MG/M3; 9192

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:STANDARD OIL 350B (CONTAINS PARAFFINS,INCL NAPHTHENES &
AROMATICS)

Fraction by Wt: 23.7%

ACGIH TLV:250 PPM (MFG)

Ingred Name:COLOR EXTENDER

Fraction by Wt: 5.28%

Ingr

ed Name:RAW LINSEED OIL
CAS:8001-26-1
RTECS #:OI9690000
Fraction by Wt: 62.6%

Ingred Name:PARAFFIN WAX
CAS:8002-74-2
RTECS #:RV0350000
Fraction by Wt: 2.54%
OSHA PEL:2 MG/M3 (FUME)
ACGIH TLV:2 MG/M3 (FUME); 9192

===== Hazards Identification =====

Effects of Overexposure:INHALATION:(HIGH CONC) ASPHYSIATION IS
POSSIBLE. SKIN/EYE:IRRITATION

===== First Aid Measures =====

First Aid:INH:PROMPTLY REMOVE TO FRESH AIR.SKIN:
WASH SKIN THOROUGHLY
W/SOAP & WATER.REMOVE CONTAMINATED CLOTHING & WAS BEFORE
REUSE.EYE:FLUSH W/WATER AT LEAST 15 MIN, GET MEDICAL ATTN IF IRRIT
PERSISTS. SWALLOW :DO NOT INDUCE VOMITING, CALL MD

===== Fire Fighting Measures =====

Flash Point:104F TCC
Lower Limits:0.8
Upper Limits:6.8
Extinguishing Media:CO*2, DRY CHEMICAL
Fire Fighting Procedures:TURN OFF IGNITION SOURCES
Unusual Fire/Explosion Hazard:LNONE

===== Accidental Release
Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION OF VICINITY
OF SPILL OR RELEASED VAPORS. CLEAN UP SPILLS AS SOON AS
POSSIBLE.ABSORB LARGE SPILLS W/CLAY, DIATOMACEOUS EARTH

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VETILATED AREA
AWAY FROM SOURCES OF IGNITION;CONTAINERS OF THIS MATERIAL SHOULD
HAVE A COMBUSTIBLE LIQUID "CAUTION" LABEL.

===== Exposure

Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED ORGANIC VAPOR RESP;USE
SELF-CONT IF CONC> TLV
Ventilation:LOCAL EXHAUST IF CONC OF VAPOR IS EXCESSIVE.
Protective Gloves:NEOPRENE/RUBBER
Eye Protection:CHEM SAFETY GOGGLES
Supplemental Safety and Health
ADD INGRED:SUSP.AGENTS,STABILIZERS,DRIERS;TOTAL 1.83%.MFG SUGGESTS TLV
OF 250 PPM (DETERMINED ON BASIS OF RELATED HYDROCARBONS)STANDARD
OIL 350B IS 97% PARAFFINS & 3% AROMATICS.

=====

= Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:311-386F
Vapor Pres:5.
Vapor Density:4.90
Spec Gravity:0.9483
Evaporation Rate & Reference:0.12 (BUAC)
Solubility in Water:NEGLIGIBLE
Percent Volatiles by Volume:28.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
MAY REACT W/STRONG OXIDIZING MATERIALS
Hazardous Decomposition Products:NORM CMBSTN:CO*2, WATER VAPOR.INCMPLT
COMBUSTION:CO

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL
REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document s

ould seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.