

PRESERVATIVE PAINT CO -- OIL STAIN-DARK REDWOOD -- 8010-00-926-9130

===== Product Identification =====

Product ID:OIL STAIN-DARK REDWOOD

MSDS Date:01/01/1985

FSC:8010

NIIN:00-926-9130

MSDS Number: BFWYJ

=== Responsible Party ===

Company Name:PRESERVATIVE PAINT CO

Address:5410 AIRPORT WAY S

Box:80387

City:SEATTLE

State:WA

ZIP:98108-1726

Country:US

CAGE:86589

=== Contractor Identification ===

Compan

y Name:PRESERVATIVE PAINT CO

Address:5410 AIRPORT WAY S

Box:80387

City:SEATTLE

State:WA

ZIP:98108-1726

Country:US

CAGE:86589

===== Composition/Information on Ingredients =====

Ingred Name:PENTACHLOROPHENOL (SARA III)

CAS:87-86-5

RTECS #:SM6300000

Fraction by Wt: 4.04%

OSHA PEL:S, 0.5 MG/M3

ACGIH TLV:S, 0.5 MG/M3; 9192

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:STANDARD OIL 350B (CONTAINS PARAFFINS,INCL
NAPHTHENES,&AROMATICS)

Fraction by Wt: 23.7%

ACGIH TLV:250 PP

M (MFG)

Ingred Name:COLOR EXTENDERS
Fraction by Wt: 5.28%

Ingred Name:RAW LINSEED OIL
CAS:8001-26-1
RTECS #:OI9690000
Fraction by Wt: 62.6%

Ingred Name:PARAFFIN WAX
CAS:8002-74-2
RTECS #:RV0350000
Fraction by Wt: 2.54%
OSHA PEL:2 MG/M3 (FUME)
ACGIH TLV:2 MG/M3 (FUME); 9192

===== Hazards Identification =====

Effects of Overexposure:INHALATION:(HIGH CONC)ASPHYXIATION IS
POSSIBLE.SKIN/EYE:IRRITATION.

===== First Aid Measures =====
=====

First Aid:INH:PROMPTLY REMOVE TO FRESH AIR.SKIN:WASH SKIN THOROUGHLY
W/SOAP & WATER.REMOVE CONTAMINATED CLOTHING & WAS BEFORE
REUSE.EYE:FLUSH W/WATER AT LEAST 15 MINS, GET MEDICAL ATTN IF IRRIT
PERSISTS.SWALLOW :DO NOT INDUCE VOMITING, CALL MD.

===== Fire Fighting Measures =====

Flash Point:104F TCC
Lower Limits:0.8
Upper Limits:6.8
Extinguishing Media:CO*2, DRY CHEMICALS
Fire Fighting Procedures:TURN OFF IGNITION

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION IN VICINITY
OF SPILL OR RELEASED VAPORS.CLEAN UP AS SOON AS POSSIBLE.ABSORB
LARGE SPILLS W/CLAY,DIATOMACEOUS EARTH

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA
AWAY FROM SOURCES OF IGNITION:CONTAINERS OF THIS MATERIAL SHOULD
HAVE A COMBUSTIBLE LIQUID "CAUTION" LABLE.

=====

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APROVED ORGANIC VAPOR RESP.;USE
SELF-CONT IF CONC > TLV

Ventilation:LOCAL EXHAUST IF CONC OF VAPOR IS EXCESSIVE

Protective Gloves:NEOPRENE/RUBBER

Eye Protection:CHEM SAFETY GOGGLES

Supplemental Safety and Health

ADD INGRED:SUSP.AGENTS,STABILIZERS,DRIERS;TOTAL1.83%.MFG SUGGESTS TLV
OF 250 PPM (DETERMINED ON BASIS OF RELATED HYDROCARBONS)STANDARD
OIL 350B IS 97% PARAFFINS & 3% AROMATICS.

====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:311-386F

Vapor Pres:5

Vapor Density:4.90

Spec Gravity:0.9483

Evaporation Rate & Reference:0.12 (BUAC)

Solubility in Water:NEGLIGIBLE

Percent Volatiles by Volume:28.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MAY REACT W/STRONG OXIDIZING MATERIALS

Hazardous Decomposition Products:NORM COMBUSTION:CO*2,WATER
VAPOR.INCMPLT COMBUSTION:CO

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL CODES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document sho

uld seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.