View NSN Online: https://aerobasegroup.es/nsn/6850-00-941-5054

GEORGE SENN COMPANY, INC -- O-C-1889 CLNG CMPD SOLVENT TECH. -- 6850-00-941-5054

Product ID:O-C-1889 CLNG CMPD SOLVENT TECH.

MSDS Date:01/01/1985

FSC:6850

NIIN:00-941-5054
MSDS Number: BFYJT
=== Responsible Party ===

Company Name: GEORGE SENN COMPANY, INC

CAGE:KO352

=== Contractor Identification ===

Company Name: GEORGE SENN COMPANY, DIV. OF GLOBE SOLVENTS

Address:220

0 E WESTMORELAND ST Box:City:PHILADELPHIA

State:PA

ZIP:19134-3229 Country:US CAGE:KO352

Company Name: GLOBE SOLVENTS CO INC

Box:City:PHILADELPHIA

State:PA Country:US

Phone:215-426-1400

CAGE:72829

======= Composition/Information on Ingredients ========

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000 Fraction by Wt: 70% OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name: METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)

CAS:75-09-2

RTECS #:PA8050000 Fraction by Wt: 25% DOT Rpt Qty:1000 LBS Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III) CAS:127-18-4 RTECS #:KX3850000 Fraction by Wt: 5% OSHA PEL:100 PPM ACGIH TLV:25PPM/100,A3 STEL:94 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS Effects of Overexposure: LACK OF COORDINATION TO UNCONSCIOUSNESS ====== First Aid M easures ============ First Aid:MOVE TO FRESH AIR, USE ARTIFICIAL RESPIRATION IF BREATHING STOPPED, ADMINISTER OXYGEN WHEN BREATHING HAS BEEN RESTORED. NEVER ADMINISTER ADRENALIN!!CALL A DOCTOR;INSTRUCT HIM NOT TO USE ADRENALIN!! ============ Fire Fighting Measures ========================= Flash Point:NLT 200F Extinguishing Media:NONE Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE ======== Accidental Release Measures ========== Spill Release Procedures: ADEQUATE VENTILATION MUST BE PROVIDED. WORKMEN PROVIDED WTH FRESH AIR MASKS OR SENT TO FRESH AIR.RECOVER FREE LIQUID, REMOVE AL IGNITION SOURCES, VENTILATE ENCLOSED AREAS, OPEN ALL WINDOWS AND DOORS. ============= Handling and Storage ========================== Handling and Storage Precautions: KEEP CONTAINERS CLOSED. KEEP AWAY FROM HEAT AND OPEN FLAMES, OR SPARKS. Other Precautions: USE ONLY WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED BR

Other REC Limits: NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

EPA Rpt Qty:1000 LBS

ACGIH TLV:50 PPM, A2; 9394

====== Exposure Controls/Personal Protection ========
Respiratory Protection:FRESH AIR SUPPLIED MASKS. Ventilation:LOCAL-YES.FACE VELOCITY 60 PPM Protective Gloves:NEOPRENE;VITON Eye Protection:GOGGLES,OR FACE SHIELD Other Protective Equipment:NEOPRENE APRON Supplemental Safety and Health THIS COMMODITY IS NOT REGULATED BY DOT,IMCO,IAT,6D AND AFR 71-4 PER STAN JAKUBOWSKI MATERIALS TO AVOID:OXYGEN,STRONG OXIDIANTS, HYDROXIDES OR SODI UM AND POTASSIUM.
========== Physical/Chemical Properties ==========
HCC:T4 Boiling Pt:B.P. Text:130 Spec Gravity:0.977 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR ===================================
Stability Indicator/Materials to Avoid:YES SEE SUPPLEMENTAL DATA Stability Condition to Avoid:ANHYDROUS ALUMINUM CHLORIDE IN THE PRESENCE OF AROMATIC COMP Hazardous Decomposition Products:CARBON MONOXIDE,HYDROGEN CHLORIDE,TRA CES OF PHOSGENE
======= Disposal Considerations ==========
Waste Disposal Methods:RECOVER FREE LIQUID,FORCE EVAPORATION OR VENTILATION,STAY UPWIND AND/OR USE PERSONAL PROTECTIVE

EATHING OF VAPORS OR CONTACT WITH SKIN.

EQUIPMENT.USE APPROVED CONTAINER TO STORE FREE LIQUID.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied

, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.