Product ID:604 ANTI RUST SPRAY, 34727(NEW FORMULATION) MSDS Date:01/01/1987 FSC:8030 NIIN:00-957-3089 **MSDS Number: BFZCC** === Responsible Party === **Company Name: SPRAYON PRODUCTS** Address:26300 FARGO AVE City:BEDFORD HEIGHTS State:OH ZIP:44146-1310 Country:US Emergency Phone Num:216-292-7400 CAGE:09800 === Contractor Identification === Company Na me:SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC. Address:26300 FARGO AVENUE Box:City:BEDFORD HEIGHTS State:OH ZIP:44146 Country:US Phone:216-292-7400 OR 216-595-8634 CAGE:09800

Ingred Name:ODORLESS MINERAL SPIRITS (CAS# 64742-89-8) (LEL=1.1) Fraction by Wt: 55% ACGIH TLV:500 PPM (MFR)

Ingred Name:2-BUTOXYETHANOL CAS:111-76-2 RTECS #:KJ8575000 Fraction by Wt: 5% OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293

Ingred Name: ISOBUTANE

(CAS# 75-28-5) (LEL=1.8) CAS:75-28-5 RTECS #:TZ4300000 Fraction by Wt: 10% ACGIH TLV:1000 PPM (MFR)

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 Fraction by Wt: 10% OSHA PEL:1000 PPM ACGIH TLV:ASPHYXIANT; 9192

Effects of Overexposure: HIGH VAP CONC IN CONF AREA IS ANESTHETIC.SKIN, UPPER RESP SYS IRRIT. POSS LIGHT-HEAD, (SEE OTHR PRECAUT

First Aid

:EYES:FLUSH W/H\*2O FOR @ LEAST 15 MIN. SKIN:WASH W/SOAP & H\*2O. INHAL:REMOVE PATIENT TO FRESH AIR. INGEST:CALL DR IMMEDIATELY. DO NOT INDUCE VOMITING.

Flash Point:PRPLNT < 20F,TOC Extinguishing Media:CO\*2,DRY CHEMICAL OR FOAM Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA,FULL PROT EQUIP.DONT(SEE SUPP DATA) Unusual Fire/Explosion Hazard:H\*2O POSS INEFFECTIVE,MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION, VENTILATE. AVOID BREATHING VAPORS & REMOVE W/INERT ABSORBENT.

 Handling and Storage Precautions: KEEP AWAY FROM CHILDREN. DO NOT PUNCTURE OR INCINERATE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME.
Other Precautions: EFTS OF OVEREXP: STAGGERING, GIDDY, POSS NAUS. HARMFUL/FATAL IF INGEST. REPORTS ASSOCIATE RPTD/PRLNG OVEREXP TO SOLVENTS W/PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.REFORMULATION OCCURED BEFORE 7-77.

======= Exposure Controls/Personal Protection ==========

Ventilation:LOCAL EXHAUST VENT TO KEEP BELOW ACCEPTABLE TLV. Protective Gloves:PRLNG/RPTD CONT Eye Protection:CHEMICAL WORKERS GOGGLES Supplemental Safety and Health EVAPORATION RATE IS FOR PROPELLANT. % VOLATILE BY WT:85. SPECIAL FIRE FIGHT PROC:SPRAY NEAR OPEN FLM. KEEP @ ROOM TEMP;HEAT MAY CAUSE

BURST

ING. DATE OF PREP:3-22-86.

HCC:V3 Boiling Pt:B.P. Text:PRPLT 1 Evaporation Rate & amp; Reference:FASTER THAN ETHER

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:DO NOT STORE ABOVE 120F. Hazardous Decomposition Products:BY OPEN FLM:CO,CO\*2

Waste Disposal Methods:D O NOT INCINERATE. DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and as sume responsibility for the suitability of this information to their particular situation.