

AMERON INC -- AMERCOAT,78 RESIN BLACK -- 8010-00-997-2610

===== Product Identification =====

Product ID:AMERCOAT,78 RESIN BLACK

MSDS Date:01/01/1987

FSC:8010

NIIN:00-997-2610

Kit Part:Y

MSDS Number: BGCKQ

=== Responsible Party ===

Company Name:AMERON INC

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:JO830

=== Contractor Identification ===

Company Name:AMERON INC

CAGE:JO830

Company Name:AMERON INTERNATIONAL PROTECTIVE COATINGS GROUP

A

Address:201 NORTH BERRY ST.

Box:City:BREA

State:CA

ZIP:92821

Country:US

Phone:714-529-1951

CAGE:55849

===== Composition/Information on Ingredients =====

Ingred Name:COAL TAR CAS# 8007-45-2

CAS:8007-45-2

RTECS #:GF8600000

Fraction by Wt: 25%

ACGIH TLV:0.2 MG/CUM

Ingred Name:EPOXY RESIN CAS# 65068-38-6

Fraction by Wt: 18%

ACGIH TLV:2 PPM(SKIN)

Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-3

RTECS #:QJ0525000

Fraction by Wt: 7%

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL;

9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 7%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL N-AMYL KETONE
CAS:110-43-0
RTECS #:MJ5075000
Fraction by Wt: 3%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9192

===== Hazards Identification =====

Effects of Overexposure:IRRIT:SKIN,MUC MEMB,EYE,RESP
SY
S.INHAL:HDCH,NAUS,DIZ,ASPHYXIA.SKIN SENSITIZATION-OTHER
PRECAUTION.

===== First Aid Measures =====

First Aid:INHAL:FRESH AIR.GIVE O*2,CPR.SKIN:WASH THOROUGHLY WITH SOAP
AND WATER.EYE:FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MIN AND
GET MEDICAL ATTENTION.LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.INGEST: DO NOT INDUCE VOMITING;CALL PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:
121F,49C SCC
Lower Limits:1.1
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT,ELECTRICAL
EQUIPMENT,SPARKS AND OPEN FLAME.WEAR SELF-CONTAINED BREATHING
APPARATUS

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION.USE
ABSORBENT CLEANUP MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOS

ED WHEN NOT IN

USE.STORE IN COOL, DRY, WELL-VENTILATED AREA.AVOID PROLONGED
BREATHING OF VAPORS, SPRAY MIST, CONTACT W/ SKIN, EYES.

Other Precautions:WEAR PROTECTIVE BARRIER CREAM ON EXPOSED
SKIN.OVEREXPOS:INHAL,INGEST,ABSORB THRU THE SKIN CAN BE
HARMFUL.KIDNEY,LIVER DAMAGE MAY OCCUR.SKIN IRRITATION ACCENTUATED
BY SUNLIGHT.

===== Exposure Controls/Personal Protection =====

Ventilation:SUFFICIENT VENTILATION TO KEEP AIR CONTAMINANT CONC 1

Spec Gravity:1.43

Evapo

ration Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID,SOLVENT ODOR

Percent Volatiles by Volume:26

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, OPEN FLAME, ARC OR
SPARKS.LIGHT:PHOTOCHEMICALLY REACTIVE

Hazardous Decomposition Products:CO,CO*2,NO*X.BURN,WELD PRODUCE COAL
TAR FUME KEEP