

CO-POLYMER CHEMICALS -- EPOXYN ENAMEL R-84-G, PART B, CLEAR -- 5970-00-998-2800

===== Product Identification =====

Product ID:EPOXYN ENAMEL R-84-G, PART B, CLEAR

MSDS Date:01/01/1987

FSC:5970

NIIN:00-998-2800

Kit Part:Y

MSDS Number: BGCLY

=== Responsible Party ===

Company Name:CO-POLYMER CHEMICALS

Address:12350 MERRIMAN ROAD

City:LIVONIA

State:MI

ZIP:48150

Country:US

Emergency Phone Num:(313) 421-0800

CAGE:13178

=== Contractor Identification ===

Company Name:C

O-POLYMER CHEMICALS INC

Address:12350 MERRIMAN RD

Box:City:LIVONIA

State:MI

ZIP:48150-1923

Country:US

CAGE:13178

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY POLYAMIDE RESIN

Fraction by Wt: 24%

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 45.6%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ALCOHOLS (TYPE NOT SPECIFIED)

Fraction by Wt:

26.6%

Ingred Name:KETONE (TYPE NOT SPECIFIED)

Fraction by Wt: 3.8%

ACGIH TLV:200 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:NOT STATED BY MFR
Effects of Overexposure:INHALATION:CAN CAUSE DIZZINESS,NAUSEA,POSSIBLE
UNCONSCIOUSNESS,ASPHYXIATION;SKIN:PROLONGED OR REPEATED CONTACT CAN
CAUSE MODERATE IRRITATION,DEFATTING OR DERMATITUS; EYES:CAN CAUSE
SEVERE EYE IRRITA
TION; INGESTION:CAN CAUSE CNS DAMAGE.
Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER

===== First Aid Measures =====

First Aid:INHAL-MOVE TO FRESH AIR,CALL MD. SKIN-WASH W/MILD SOAP &
WATER.WASH CLOTHES BEFORE REUSE,EYES-FLUSH WITH WATER FOR 15
MIN-CALL DR IMMEDIATELY.INGEST-DO NOT INDUCE VOMITING.KEEP PERSON
WARM & QUIET & G ET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point
Method:TCC
Flash Point:80F/26.7C
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:FLASHBACK ALONG VAPOR TRAIL MAY OCCUR;
VAP MAY EXPL. IF IGNITED IN AN ENCLOSED AREA.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP AWAY FROM OPEN FLAME OR SPARKS.SOAK UP
WITH ABSORBENT MATERIAL.PLACE IN APPROVED DOT CO

CONTAINERS FOR
SHIPMENT TO DISPOSAL AREA.
Neutralizing Agent:NOT KNOWN

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXCEED TLV,NIOSH/MSHA APPRO SELF-CONTAINED BREATHING
APP
(POSITIVE MODE)
Ventilation:PROVIDE MECHANICAL(GEN/LOCAL EXHAUST)VENT TO MAINTAIN