

RIDGE TOOL COMPANY DIV EMERSON ELECTRIC -- RIDGID NUCLEAR THREAD CUTTING OIL. --
9150-01-013-5281

===== Product Identification =====

Product ID:RIDGID NUCLEAR THREAD CUTTING OIL.

MSDS Date:03/18/1990

FSC:9150

NIIN:01-013-5281

MSDS Number: BGDJG

=== Responsible Party ===

Company Name:RIDGE TOOL COMPANY DIV EMERSON ELECTRIC

Address:400 CLARK STREET

City:ELYRIA

State:OH

ZIP:44035-6108

Country:US

In

fo Phone Num:216-323-5581

Emergency Phone Num:216-323-5581

CAGE:50893

=== Contractor Identification ===

Company Name:RIDGE TOOL COMPANY

Address:400 CLARK STREET

Box:City:ELYRIA

State:OH

ZIP:44036-2023

Country:US

Phone:800-519-3456

CAGE:50893

===== Composition/Information on Ingredients =====

Ingred Name:PARAFFINIC MINERAL OIL

CAS:64742-50-3

OSHA PEL:5MG/M*3 (MIST)

ACGIH TLV:5MG/M*3 (MIST)

Ingred Name:FLOUR OF SULFUR

CAS:7704-34-9

RTECS #:WS4250000

Ingred Name:ANIMAL AND VEG

ETABLE FAT

Ingred Name:ANTIFOAM AGENTS (TYPE UNIDENTIFIED)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:CAUSES IRRITATION. MAY BE SKIN
DEFATTER UPON PROLONGED OR REPEATED CONTACT.

Effects of Overexposure:OIL MIST INHALATION MAY CAUSE DIZZINESS,NAUSEA
& DIFFICULTY IN BREATHING.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH SENSITIVE DRY
SKIN.

=====

==== First Aid Measures =====

First Aid:IN CASE OF CONTACT:IMMEDIATELY FLUSH EYES WITH PLENTY OF
WATER FOR AT LEAST 15 MINUTES,CALL A PHYSICIAN. WASH SKIN WITH SOAP
& WATER. IF SWALLOWED,DO NOT INDUCE VOMITING. GET MEDICAL
ATTENTION. REMOVE FLUID SOAKED CLOTHING & SHOES. LAUNDERBEFORE
REUSE. IF INHALED,REMOVE TO FRESH AIR & GIVE CPR IF NECESSARY. GET
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Met

hod:PMCC

Flash Point:340F,171C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:HOT VAPORS FORM EXPLOSIVE MIXTURES WITH
AIR.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT USE WATER. SOAK UP WI

TH SAND, EARTH OR
OTHER INERT MATERIAL. PUT IN A SUITABLE CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING MIST OR
VAPORS.

Other Precautions:EMPTY CONTAINERS RETAIN PRODUCT RESIDUE. FOLLOW LABEL
WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

===== Exposure Controls/Personal Protection =====

Respira
tory Protection:NIOSH APPROVED RESPIRATOR IF EXPOSED TO HOT
VAPOR OR MIST.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS REQD TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH AFTER HANDLING.

Supplemental Safety and Health

NUCLEAR OIL HAS THE ADDITIONAL P/N'S

41565-1QT;41575-5GL;41580-30GL;41585-55GL.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P.

Text:480F,249C

Melt/Freeze Pt:M.P/F.P Text:0F,-18C MAX

Vapor Pres:0.01

Vapor Density:1

Spec Gravity:0.87

Evaporation Rate & Reference:1 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH MILD PETROLEUM ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS AND OXIDANTS

Stability Condition to Avoid:SPARKS AND OPEN FLAMES

Hazardous Decomposition Product

s:CO, CO*2, OXIDES OF SULFUR

===== Disposal Considerations =====

Waste Disposal Methods:BURY IN AN APPROVED LANDFILL OR INCINERATE IAW
FEDERAL,STATE & LOCAL REGULATIONS. AVOID CONTAMINATION OF SEWERS &
WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants th
is information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.