

DOW CORNING CORP. -- CHO-BOND PRIMER 1086(DOW CORNING 1204 PRMR) -- 8040-01-015-3805

===== Product Identification =====

Product ID:CHO-BOND PRIMER 1086(DOW CORNING 1204 PRMR)

MSDS Date:07/20/1987

FSC:8040

NIIN:01-015-3805

MSDS Number: BGDMY

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:SOUTH SAGINAW RD.

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:PARKER HANNIFIN CORPORATION CHOMERICS DIVISION

Address:77 DRAGON COURT

Box:City:WOBURN

State:MA

ZIP:01888

Country:US

Phone:617-935-4850

CAGE:18565

=====

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 65%

OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 19%.

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 2%.

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA R

pt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-METHOXYETHYLORTHOSILICATE(EXPOSURE LIMITS BASED ON
2-METHOXYETHANOL FORMATION VIA HYDROLYSIS(WATER/HUMID AIR)).

Fraction by Wt: 4%.

OSHA PEL:25 PPM

ACGIH TLV:S, 5 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYE,SKIN & RESPIRATORY

IRRITANT; INHAL: SHORT VAPOR

EXPOSURE MAY CAUSE DROWSINESS.

CHRONIC: POSSIBLE INJURY TO BLOOD,LUNGS,LIVER,KIDNEYS & NERVOUS

SYSTEM DEPENDING ON CONC. & EXPOSURE LENGTH. 2 -METHOXYETHANOL MAY

FORM UPON HYDROLYSIS & IS ABLE TO CAUSE ANIMAL BIRTH DEFECT

Effects of Overexposure:EYES:DIRECT CONTACT IRRITATES;MAY BE SERIOUS

W/REDNESS,SWELLING,& SOME CORNEAL INJURY LASTING SEVERAL DAYS TO A

WEEK; SKIN:NO KNOWN ADVERSE EFFECT FOR SINGLE RELATIVELY SHRT

EXPOS.;SEVERAL REPTD. PROL NGD EXPOS(24-48HR) MAY IRRITA

TE;
INHAL:SHORT VAPOR EXPOS. MAY CAUSE DROWSINESS & IRRITATE
NOSE/THROAT; ORAL:MAY INJURE!
Medical Cond Aggravated by Exposure:PROLONGED TOLUENE OVEREXPOSURE MAY
INJURE BLOOD, LUNGS, LIVER, KIDNEYS & NERVOUS SYSTEM & MAY
AGGRAVATE EXISTING EYE, SKIN & RESPIRATORY DISORDERS.

===== First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH W/WATER. GET IMMEDIATE MEDICAL ATTN;
SKIN: IMMEDIATELY WIPE OFF & FLUSH W/WATER.; INHAL: REMOVE TO F
RESH
AIR. GET IMMEDIATE MEDICAL ATTN IF ILL EFFECTS PERSIST.; ORAL: GET
IMME D. MEDICAL ATTN. IF LARGE AMTS. SWALLOWED. DO NOT INDUCE
VOMITING. NOTE:INHALING LIQUID WHILE VOMITING CAN INJURE LUNGS
SERIOUSLY. KEEP HEAD LOWER THAN HIPS TO PRVT LIQ. ASPIRATION TO
LNG.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:59F/15C
Lower Limits:1. %
Upper Limits:7. %
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOA
M
Fire Fighting Procedures:SELF-CONTND BRTHNG APPART. & PROTECTIVE
CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR & CAN TRAVEL
ALONG GROUND TO REMOTE IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES & WEAR PROPER
PROTECTION EQUIPMENT. FOR SPILL, USE ABSORBENT MATERIAL TO COLLECT
& CONTAIN FOR SALVAGE OR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED & AWAY FROM
HEAT, SPARKS, & OPEN FLAME.
Other Precautions:STATIC ELECTRICITY MAY ACCUMULATE & CREATE A FIRE
HAZARD. GROUND FIXED EQUIPMENT. BOND & GROUND TRANSFER CONTAINERS &
EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR TYPE. //USE RESPIRATORY PROTECTION
UNLESS LOCAL EXHAUST VENTILATION IS A

DEQUATE OR AIR SAMPLING DATA

SHOW EXPOSURES ARE WITHIN TLV & PEL GUIDELINES.

Ventilation:LOCAL EXHAUST & GENERAL MECHANICAL VENTILATION:
RECOMMENDED.

Protective Gloves:USE IMPERVIOUS TYPE: PVC/NITRILE

Eye Protection:USE CHEMICAL WORKER GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING: APRONS, BOOTS, ETC.

Work Hygienic Practices:REMOVE GROSS AMT. OF ANY CHEMICAL FROM SKIN AS
SOON AS PRACTICAL,ESPECIALLY BEFORE EATING OR SMOKING.

Supplemental Safety and Health

NOTE: AVOID BREATHI

NG VAPORS & EYE & SKIN CONTACT. USE ONLY W/ADEQUATE
VENTILATION. DO NOT TAKE INTERNALLY.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:210F/99C

Vapor Pres:25 MM

Vapor Density:>1

Spec Gravity:0.77 @ 77F

Evaporation Rate & Reference:(ETHER = 1), < 1.

Appearance and Odor:LIQUID, LIGHT STRAW; SOLVENT ODOR

Percent Volatiles by Volume:95.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S

OXIDIZING MATERIAL CAN CAUSE REACTION. WATER OR MOISTURE.

Stability Condition to Avoid:EXPOSURE TO AIR UNTIL READY TO USE.

Hazardous Decomposition Products:METAL OXIDES, SILICON DIOXIDE, CARBON
DIOXIDE, & TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:REVIEW ALL LOCAL,STATE & FEDERAL REGULATIONS
CONCERNING HEALTH & POLLUTION TO DETERMINE APPROVED DISPOSAL
PROCEDURES. CONTACT DOW-CORNING IF
THERE ARE ANY DISPOSAL
QUESTIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this i

nformation to their
particular situation.