

CRC CHEMICALS,USA -- CRC RED URETHANE SEAL COAT, P/N 2044 -- 5970-01-017-5738

===== Product Identification =====

Product ID:CRC RED URETHANE SEAL COAT, P/N 2044

MSDS Date:01/01/1987

FSC:5970

NIIN:01-017-5738

MSDS Number: BGDSY

=== Responsible Party ===

Company Name:CRC CHEMICALS,USA

Address:885 LOUIS DRIVE

City:WARMINSTER

State:PA

ZIP:18974-2820

Country:US

Info Phone Num:215-674-4300

Emergency Phone Num:215-674-4300

CAGE:GO966

=== Contractor Identification ===

Company Name:CRC CHEMICALS,USA

CAGE:GO966

Company Name:CRC INDUSTRIES, INC.

Address:885 LOUIS DRIVE

Box:City:WARMINSTER

State:PA

ZIP:18974-2820

Country:US

Phone:215-674-4300/800-424-9300

CAGE:10136

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA

Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450 STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:ISOBUTANE/PROPANE MIXTURE; SEE SUPPL DATA FOR NIOSH-6
COMPONENT.
ACGIH TLV:1000PPM

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN: IRRITATION. VAPORS:
HEADACHE,N
AUSEA,DIZZINESS,DRYNESS OF THROAT,VOMITING.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,CALL PHYSICIAN. SKIN: FLUSH
WITH WATER. INHALATION: REMOVE TO FRESH AIR,GIVE ARTIFICIAL
RESPIRATION IF NEEDED,CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM.
Fire Fighting Procedures:PRESSURE DAMAND SCBA & FULL PROTECTIVE
CLOTHIN
G.
Unusual Fire/Explosion Hazard:AEROSOL CANS MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:SECURE SOURCES OF IGNITION. LARGE SPILLS MAY
BE PICKED UP WITH NON-SPARKING TOOLS. SMALL QUATITIES MAY BE PICKED
UP WITH ABSORBANT MATERIAL. PROVIDE RESPIRATORY PROTECTION IF
REQUIRED.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE NE

AR OPEN FLAME OR STORE

AEROSOL CAN ABOVE 120F/48C. DO NOT PUNCTURE OR INCINERATE.

Other Precautions:NO SMOKING,ARC WELDING,OR HOT SURFACES IN AREA OF
USE,MAY CAUSE FORMATION OF HCL OR PHOSGENE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.

Ventilation:MECHANICAL

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

MSDS FM MFR UNDATED; NIOSH 6 COMPONENT: RED IRON
OXIDE,2.4%.

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Spec Gravity:1.123

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED VISCOUS LIQUID-PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:84

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXCESSIVE HEAT,IGNITION SOURCES

Hazardous Decomposition Products:AT HIGH TEMP P

OISONOUS GASES ARE
FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.
DO NOT INCINERATE AEROSOL CANS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims a

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.