BEL-RAY COMPANY, INC -- MOLYLUBE SILICONE LH-10 GREASE -- 9150-01-019-0669 Product ID:MOLYLUBE SILICONE LH-10 GREASE MSDS Date:01/01/1985 FSC:9150 NIIN:01-019-0669 MSDS Number: BGDWY === Responsible Party === Company Name: BEL-RAY COMPANY, INC Emergency Phone Num:201-938-2421 CAGE:KO301 === Contractor Identification === Company Name: BEL-RAY COMPANY INC. Address:1201 BOWMAN AVE Box:526 City:FARMINGDALE State:NJ ZIP:07727 Country: US Phone:732-938-2421 CAGE:12474 Company Name: BEL-RAY COMPANY, INC. Box:526 CAGE:KO301 ======= Composition/Information on Ingredients ========

Ingred Name: MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000 Fraction by Wt: 10.0%

OSHA PEL:10 MG/M3 TDUST (MO) ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name: SILICA Fraction by Wt: 7.0%

ACGIH TLV:30 MG(DUST)/CUM

Ingred Name: SOLIDS, HAZARD UNKNOWN, UNIDENTIFIED; % WT BY DIFFERENCE

Fraction by Wt: 83.0%

====== Hazards Identif

ication ===========
Effects of Overexposure:MFR STATES THAT NO KNOWN ADVERSE EFFECTS FROM EXPOSURE
======================================
First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER. INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.
======================================
Flash Point:530F-COC Lower Limits:1.0% Upper Limits:6.0% Extinguishing Media:CO*2, FOAM, DRY CHEM & H*20 FOG. Fire Fighting Procedures:FOR ENCLOSED AREAS USE AIR SUPPLIED RESCUE EQUIPMENT Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:USE PROTECTV GLOVES FOR CLEAN-UP; WIPE,CONTAIN & RECOVER.PLACE IN COVERED CONTAINERS.
======================================
Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT . KEEP CONTAINERS TIGHTLY CLOSED Other Precautions:NONE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:NORMAL ROOM VENTILATION. Protective Gloves:AS REQUIRED Eye Protection:AS REQUIRED Other Protective Equipment:USE GOOD INDUSTRIAL HYGIENIC PRACTICES. Supplemental Safety and Health MSDS FM MFR DATED:11-30-81
========= Physical/Chemical Properties ==========
HCC:V6 Boiling Pt:B.P. Text:IBP >60

0F

Vapor Pres:.02 Vapor Density:>10 Spec Gravity:1.2

Solubility in Water: NEGLIGIBLE Appearance and Odor: GREASE. Percent Volatiles by Volume: 1.0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS SUCH AS CONCENTRATED OXYGEN/CHLORINE Hazardous Decomposition Products:CO,CO*2 & SULFUR COMPOUNDS.

====== Disposal Considerations ==========

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOS AL. HANDLE &

DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS. MFR NOTES: REMOVE TO LANDFILL OR USE LICENSD WASTE OIL DISPOSL CONTCTR.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability fo

r its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.