

TEXSTAR AUTOMOTIVE GROUP -- GEAR LUBRICANT (80W/90) -- 9150-01-035-5392

===== Product Identification =====

Product ID:GEAR LUBRICANT (80W/90)

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5392

MSDS Number: BGGJW

=== Responsible Party ===

Company Name:TEXSTAR AUTOMOTIVE GROUP

Emergency Phone Num:314-521-3900

CAGE:1ER44

=== Contractor Identification ===

Company Name:TEXSTAR AUTOMOTIVE GROUP INC

Address:9060 LATTY AVE

Box:City:ST LOUIS

State:MO

ZIP:63134-1027

Country

:US

Phone:314-521-3900

CAGE:1ER44

===== Composition/Information on Ingredients =====

Ingred Name:LUBRICATING OIL

===== Hazards Identification =====

Effects of Overexposure:IRRITANT FROM PROLONGED/REPEATED EXPOSURE TO SKIN.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WARM WATER, THOROUGHLY.

===== Fire Fighting Measures

=====

Flash Point:430F, 221.1C,COC

Lower Limits:1

Upper Limits:6

Extinguishing Media:FOAM, DRY CHEMICAL, CO*2, WATER FOG OR SPRAY.

Fire Fighting Procedures:RESPIRATORY PROTECTION REQUIRED.

Unusual Fire/Explosion Hazard:FUMES, SMOKE, OXIDES OF SULFUR, NITROGEN & CO*2.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID. ADD ABSORBENT SUCH AS SAND, EARTH, OR SAWDUST TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT

OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING. ADVISE
AUTHORITIES IF PRODUCT HAS ENTE RED SEWERS, WATERCOURSES OR
EXTENSIVE LAND AREA.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN
USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG
OXIDANTS.

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL SOAKED CLOTHING
& LAUNDER BEFORE REUSE. DISCARD OIL SOAKED SHOES. WAS
H SKIN WITH
SOAP AND WATER AFTER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA AIR-SUP RESP IF WORKING IN CONFINED
OR CLOSED AREA.

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS-SEE SUPP DATA

Protective Gloves:CHEM RESISTANT

Eye Protection:CHEM SPLASH GOG/FACE SHLD

Other Protective Equipment:USE CHEM RESISTANT APRON OR OTHER CLOTHING
TO AVOID CONTACT

Supplemental Safety and Health

CONTAINER SIZE: 1 QT. VP: 60 F

PM HOOD OR

FACE VELOCITY FOR CONFINED SPACES. MFR ADDRESS: 9060 LATTY AVENUE,
ST. LOUIS MO, 63134.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:675F, 357C

Vapor Density:>12

Spec Gravity:0.88

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID, MILD HYDROCARBON ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

LIQUID CHLORINE,CONC O

*2,NA/CA HYPOCHLORITE- STRONG OXIDANTS

Stability Condition to Avoid:STRONG OXIDANTS

Hazardous Decomposition Products:FUMES,SMOKE,CO & SULFUR OXIDES IN
INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS DISPOSING ABSORBENT MATERIAL IN
AN APPROVED WASTE DISPOSAL SITE OR FACILITY. WASTE DISPOSAL METHOD
MUST BE IAW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compi
ling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.