

MOBIL OIL CORP -- MOBILUBE HD 85W-140, MIL-L-2105C -- 9150-01-035-5395

===== Product Identification =====

Product ID:MOBILUBE HD 85W-140, MIL-L-2105C

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5395

MSDS Number: BGGNS

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Emergency Phone Num:(212) 883-4242

CAGE:1E969

=== Contractor Identification ===

Company Name:MOBIL CORP

Address:150 E 42ND ST

Box:

City:NEW YORK

State:NY

ZIP:10017-5612

Country:US

Phone:212-883-4242

CAGE:57635

Company Name:MOBIL OIL CORP

Address:530 EAST SWEDES FORD ROAD

Box:1031

City:VALLEY FORGE

State:PA

ZIP:19482

Country:US

Phone:703-849-3265

CAGE:1E969

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: >90%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES &/OR OTHER INGRED

F

reaction by Wt: PINT INGEST,IMMED GIVE  
1TO 2 GLASS ES WATER,CALL MD FOR WAY TO INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:400F COC  
Extinguishing Media:CO\*2,FOAM, DRY CHEMICAL  
Fire Fighting Procedures:FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIA  
TOMACEOUS EARTH OR OTHER ABSORBENT. SHOVEL UP & DISPOSE OF IN APPROVED HAZARDOUS WASTE DISPOSAL FACILITY. U.S. COAST GUARD REG REQUIRE IMMED REPORTING OF S PILLS THAT COULD REACH WATERWAYS/INTERMIT DRY CRKS

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRCAUTIONS REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR STATES NO SPECIAL REQUIREMENTS UNDER NORMAL U  
SE W/ADEQ VENTIL.  
Protective Gloves:OIL IMPERVIOUS  
Eye Protection:NORMAL I.H. PRACTICES  
Supplemental Safety and Health  
MFR STATES HARMFUL CONC OF MISTS &/OR VAP ARE UNLIKELY TO BE ENCOUNTERED THROUGH ANY CUSTOMARY OR REASONABLY FOR SEEABLE HANDLING, USE OR MISUSE OF THIS PRODUCT. VAP PRESSURE:MM HG 20C  
600F  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:ASTM 7.0 LIQUID, MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials t

o Avoid: YES

STRONG OXIDIZERS

Stability Condition to Avoid: STRONG OXIDATION

Hazardous Decomposition Products: CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: MFR RECM DISSOLVE WASTE IN A SOLVENT & DISPOSE BY SUPERVISED INCINERATION IN COMPLIANCE W/APPROPRIATE REGULATIONS. DISPOSAL MUST BE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use

by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.