

KENDALL REFINING COMPANY, DIV OF WITCO CHEM. CORP -- KENDALL NS-MP HYPOID GEAR
LUBRI,ALL SAE GRA -- 9150-01-035-5396

=====
===== Product Identification =====

Product ID:KENDALL NS-MP HYPOID GEAR LUBRI,ALL SAE GRA

MSDS Date:06/20/1986

FSC:9150

NIIN:01-035-5396

MSDS Number: BGGQN

=== Responsible Party ===

Company Name:KENDALL REFINING COMPANY, DIV OF WITCO CHEM. CORP

Address:77 NORTH KENDALL AVENUE

City:B

RADFORD

State:PA

ZIP:16701

Info Phone Num:814-368-6111

Emergency Phone Num:814-368-6111

CAGE:KENDA

=== Contractor Identification ===

Company Name:KENDALL REFINING COMPANY

Address:77 N. KENDALL AVE

Box:2000

City:BRADFORD PA.

State:PA

ZIP:16701

Country:US

Phone:814-368-6111

CAGE:KENDA

Company Name:WITCO CHEMICAL CORP,KENDALL REFINING CO. DIVISION

Address:77 N KENDALL AVENUE

Box:2000

City:BRADFORD

State:PA

ZIP:16701-1726

Country:US

Phone:814-368-6111

CAGE:75273

=====
===== Composition/Informati

on on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON

Fraction by Wt:

Other REC Limits:N/K

OSHA PEL:

ACGIH TLV:

Ingred Name:ADDITIVES

Fraction by Wt:

Other REC Limits:N/K

OSHA PEL:

ACGIH TLV:

===== Hazards Identification =====

LD50 LC50 Mixture:N/K

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF OVEREXPOSURE SECTION .

Explanation of Carcinogenicity:N/A

Effects of Overexpos

ure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DERMATITIS.

Medical Cond Aggravated by Exposure:N/K

===== First Aid Measures =====

First Aid:EYES:FLUSH IMMED W/ LGE AMTS OF WATER FOR AT LEAST 15 MIN AND CALL PHYSICIAN. INHALATION:REMOVE TO FRESH AIR.SUPPORT BREATHING (GIVE O*2/ARTIFICIAL RESPIRATION)CALL PHYSICIAN. INGESTION:CALL PHY SICIAN. IMMEDIATELY. SKIN:REMOVE EXCESSWITH CLOTH/PAPER.WASH THOROUGHLY WITH SOAP & WATER.

=====

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:350F/177C

Lower Limits:NT APPLICABL

Upper Limits:NT APPLICABL

Extinguishing Media:DRY CHEMICAL OR WATERFOG OR CO*2 OR FOAM. EXPOSED MATERIAL MAY BE COOLED WITH WATER.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . DO NOT USE WATER EXCEPT AS FOG.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill R

Release Procedures:TRANSFER BULK OF MIX INTO ANOTHER CONTAINER.ABSORB RESIDUE W/AN INERT MATL SUCH AS EARTH, SAND,/VERMICULITE.SWEEP UP AND DISPOSE AS SOLID WASTE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS .

Neutralizing Agent:N/K

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT HANDLE OR STORE AT TEMPERATURES OVER 100F/38C.

Other Precautions:N/K

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE IF VAPOR CONCENTRATION EXCEEDS PERMISSIBLE EXPOSURE LIMIT

Ventilation:LOCAL IF NECESSARY TO MAINTAIN ALLOWABLE PEL(PERMISSIBLE EXPOSURE LIMIT) OR TLV (THRESHOLD LIMIT VALUE)

Protective Gloves:NEOPRENE TYPE

Eye Protection:CHEMICAL SAFETY GOGGLES

Other Protective Equipment:NONE

Work Hygienic Practices:N/K

Supplemental Safety and Health

PCT VOLT-VOL:N,VOLT BY WEIGHT:0.RT OF ENTRY:ACCORDING TO MFG:TLV FOR

PRODUCT IF USED IN APPLI WHERE MIST MAY BE GENERATED,OBSERVE A TWA/PEL OF 5 MG/M3 FOR MINERAL OIL MIST (OSHA AND ACGIH).

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:626F, 330C

Melt/Freeze Pt:M.P/F.P Text:NOT APPLIC

Decomp Temp:Decomp Text:N/K

Vapor Pres:0

Vapor Density:NT VOLATIL

Spec Gravity:0.87 TO 0.91

pH:NT APP

Evaporation Rate & Reference:0 METHOD:N/K

Solubility in Water:0 AT 20C

Appearance and Odor:VISCOUS

LIQUID, PUNGENT, SULFUR TYPE, GREEN TO BROWN

Percent Volatiles by Volume:N/K-FP

Corrosion Rate:

=====
===== Stability and Reactivity Data =====
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS SUCH AS HYDROGEN PEROXIDE, BROMINE, AND CHROMIC ACID.

Stability Condition to Avoid:N/K

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE FROM BURNING.OXIDES OF PHOSPHORUS,OXIDES OF SULFUR.

=====
===== Disposal Considerations =====
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.