

FISKE BROTHERS REFINING CO. -- FISKE'S 722 OIL -- 9150-01-048-9554

===== Product Identification =====

Product ID:FISKE'S 722 OIL

MSDS Date:11/01/1985

FSC:9150

NIIN:01-048-9554

MSDS Number: BGHYB

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Address:129 LOCKWOOD STREET

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Preparer's Name:ROBERT J.SIBILIA

CAGE:9N579

=== Contractor Identif

ication ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

CAGE:6A908

===== Composition/Information on Ingredients =====

=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')
CAS:8012-95-1
RTECS #:PY8030000
Other REC Limits:5MG/CUM AS OILMIST
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:UNIDENTIFIED COMPONENTS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN OR
RESPIRATORY TRACT. CHRONIC:NO DATA AVAILABLE,POSSIBLE DERMATITIS.
Effects of Overexposure:MAY CAUSE IRRITATION OF SKIN,EYES, RESPIRATORY
TRACT;LOW ORDER OF TOXICITY.
Medical Condition Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

===== First Aid Measures =====

First Aid:EYES:WASH WITH PLENTY OF WATER;CALL A PHYSICIAN. SKIN:WASH
WITH SOAP & WATER. INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:275F/135C
Low
Vapor Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM,DRY CHEMICAL,CO2,WATER SPRAY
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.
Unusual Fire/Explosion Hazard:DO NOT STORE WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE
INERT ABSORBENT MATERIAL & RECOVER FOR PROPER DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED
AREA. KEEP AWAY FROM HEAT,OPEN FLAMES.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPOR/MIST IF ABOVE TLV/PEL.

Ventilation:LOCAL/GENERAL TO MAINTAIN BELOW TLV/PEL

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Oth

er Protective Equipment:FULL SKIN & EYE PROTECTION

Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;DO NOT BREATHE
VAPORS/MIST.

Supplemental Safety and Health

MSDS RECEIVED BY DGSC-SLM:MARCH 4, 1988, ORIGINALLY AND AGAIN NOVEMBER,
1993.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F/288C

Vapor Pres:5.0

Spec Gravity:0.81

Evaporation Rate & Reference: