

HUGHSON CHEMICALS -- M200 -- 8030-01-054-7226

===== Product Identification =====

Product ID:M200

MSDS Date:01/01/1985

FSC:8030

NIIN:01-054-7226

MSDS Number: BGJJM

=== Responsible Party ===

Company Name:HUGHSON CHEMICALS

Emergency Phone Num:(814) 868-3641

CAGE:GO815

=== Contractor Identification ===

Company Name:G AND D AIRCRAFT PARTS INC

Address:1801 MT VERNON AVE

Box:City:POMONA

State:CA

ZIP:91768-3301

Country:US

Phone:714-623-3835

CAGE:30670

Company Name:HUG

HSOON CHEMICALS

Box:10038

CAGE:GO815

===== Composition/Information on Ingredients =====

Ingred Name:METHYL N-BUTYL KETONE (2-HEXANONE)

CAS:591-78-6

RTECS #:MP1400000

Fraction by Wt: 79.8%

OSHA PEL:100 PPM

ACGIH TLV:S, 5 PPM; 9293

===== Hazards Identification =====

Effects of Overexposure:INTOXICATION EFFECT FROM AROMATIC SOLVENT  
VAPORS.

===== First Aid Measures =====

First Aid:WASH SKIN THOROUGHLY;

IF SWALLOWED DO NOT INDUCE VOMITING!  
CALL PHYSICIAN.

===== Fire Fighting Measures =====

Lower Limits:1.2  
Upper Limits:8.0  
Extinguishing Media:FOAM, DRY CHEMICAL CO\*2,  
Fire Fighting Procedures:VAPORS EVOLVED WHEN HEATED ARE SKIN IRRITANT.  
AVOID CONTACT.  
Unusual Fire/Explosion Hazard:FIRE HAZARD - DANGEROUS RATED WHEN  
EXPOSED TO HEAT OR FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID PROLONGED BREATHING OF VAPORS: REMOVE  
SOURCES OF IGNITION; CLEAN UP SPILL IN MANNER FOR ANY STANDARD  
FLAMMABLE PAINT.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL STORAGE FOR FLAMMABLE LIQUIDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:POSITIVE AIR VENT. AIR SUPPLIED HOOD OR CHEM  
CANISTER FACE MASK.  
Protective Gloves:YES  
Eye Protection:YES  
Other Protective Equipment:AS REQUIRED TO AVOID PROLONGED SKIN CONTACT.  
Supplemental Safety and Health  
PART B FOR TWO OTHER PRODUCTS (CHEMGLAZE M213 & CHEMGLAZE M313)KEY1:F4.

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:256 RO 266F  
Vapor Pres:10  
Vapor Density:3.45  
Spec Gravity:0.8400  
Evaporation Rate & Reference:1.0 (N-BUAC)  
Solubility in Water:MODERATE  
Appearance and Odor:CLEAR YELLOW LIQUID; KETONE ODOR  
Percent Volatiles by Volume:82.8

===== Stability and Re

activity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO & CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FED., STATE & LOCAL  
REGULATIONS FOR FLAMMABLE MATERIALS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner w

hatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.