

DOW CORNING CORPORATION -- MOLYKOTE 55 M GREASE. -- 9150-01-066-1823

=====
Product Identification
=====

Product ID:MOLYKOTE 55 M GREASE.

MSDS Date:11/15/1985

FSC:9150

NIIN:01-066-1823

MSDS Number: BGKBK

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:SOUTH SAGINAW ROAD,

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

Pr

eparer's Name:JACK L.SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:GREASE SILICONE (LUBRICANT)
Fraction by Wt: 100%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:MAY CAUSE TEMPORARY
DISCOMFORT;SKIN:SLIGHT IRRITATION. CHRONIC:NO KNOWN ADVERSE CHRONIC
HEALTH EFFECTS.

Effects of Overexposure:EYES:MAY CAUSE TEMPORARY
DISCOMFORT;SKIN:SEVERAL REPEATED PR
OLONGED EXPOSURES MAY CAUSE
SLIGHT IRRITATIO;INHALATION:NO IRRITATION TO NOSE OR THROAT
EXPECTED;NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS.

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:>250F/121C
Extinguishing Media:WATERFOG,CO*2,DRY CHEMICAL,FOAM
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN FIRES.
Unusual Fire/Explosion Hazard:NONE KNOWN TO MFR.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE THE
PRODUCT AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL LIKE
RESIDUES.

=====
Handling and Storage
=====

=====

Handling and Storage Precautions:KEEP IN COOL DRY AREA;USE REASONABLE CARE AND CAUTION.

Other Precautions:TRACES OF BENZENE,FORMALDEHYDE,AND OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 150 C IN THE PRESENCE OF AIR;PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATRUES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR IF NEEDED.UNDER NORMAL CONDITIONS ON LY ADEQUATE VENTILATION IS REQUIRED.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:NEOPRENE

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS.WASH THOROUGHLY AFTER EACH USE.WASH BEFORE DRINK,EAT OR SMOKE

Supplemental Safety and Health

MSDS DATED NOVEMBER 15,1985.AVOID SMOKING,EATING DRINKING IN WORK AREA.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F/149C

Vapor Pres: