

DEFT CHEMICAL COATINGS -- 03-GY-60 COMPONENT I -- 8010-01-078-9281

===== Product Identification =====

Product ID:03-GY-60 COMPONENT I

MSDS Date:01/01/1985

FSC:8010

NIIN:01-078-9281

Kit Part:Y

MSDS Number: BGKSV

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

CAGE:EO418

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC

.  
Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:CELLOSOLVE ACETATE

RTECS #:FJ4375000

Fraction by Wt: 24%

ACGIH TLV:5 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 8%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/300STEL;9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ing

red Name:ETHYL ACETATE  
RTECS #:KQ4900000  
Fraction by Wt: 2.5%  
ACGIH TLV:400 PPM

===== Hazards Identification =====

Effects of Overexposure:INHALE-ANESTHETIC;IRRITATE RESPIR TRACT &  
NERVOUS SYSTEM. PRIMARY IRRITANT TO EYE & SKIN.

===== First Aid Measures =====

First Aid:FUMES-REMOVE FROM EXPOSURE;RESTORE BREATHING;KEEP WARM &  
QUIET;MEDICAL ATTENTION. EYES-FLUSH W LG AMTS OF WATER FOR 15 MIN.  
GET MED HELP. SKIN  
-WASH WITH WATER. REMOVE CONTAMINATED CLOTHING.  
CONSOLT PH YSICIAN.

===== Fire Fighting Measures =====

Flash Point:24F, -4C TCC  
Extinguishing Media:CO2, FOAM OR DRY CHEM. CLASS B EXTINGUISHER.  
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT.INC SELF-CONT  
BREATHING APPARA  
Unusual Fire/Explosion Hazard:KEEP CONT CLOSED.CLOSED CONT. MAY EXPLODE  
IF EXPOSED TO XS HEAT. ISOLATE FROM IGNITION SOURCES

===== Accidental Release Measure  
s =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. AVOID BREATHING  
VAPORS. VENTILATE AREA. CONTAIN & REMOVE W INERT ABSORBENT &  
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE LGE QUANTITIES IN BLDGS COMPLY W  
OSHA 1910.106  
Other Precautions:KEEP TIGHTLY CLOSED. DO NOT STORE NEAR HEAT, SPARK,  
OR FLAMES. STORE IN WELL VENTILATED AREAS PREVENT PROLONGED OR  
REPEATED BREATHING

OF FUMES. CAN CAUSE ALLERGIC REACTIONS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR  
Ventilation:IN ACCORD W OSHA 29CFR PART 1910.94  
Protective Gloves:NEOPRENE  
Eye Protection:SAFETY W SPLASH GOARDS  
Other Protective Equipment:CLEAN, LOGN SLEEVE & LONG LEG CLOTHING  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3  
Boiling Pt:B.P. Text:168F,76C  
Vapor Pres:23  
Vapor Den  
sity:>AIR  
Spec Gravity:1.2  
Evaporation Rate & Reference: