

DEFT INC CHEMICAL COATING DIV -- MIL-C-83286, G/S-E, GRAY 36081, 03GY245 --
8010-01-084-6963

===== Product Identification =====

Product ID:MIL-C-83286, G/S-E, GRAY 36081, 03GY245

MSDS Date:01/01/1987

FSC:8010

NIIN:01-084-6963

Kit Part:Y

MSDS Number: BGLBC

=== Responsible Party ===

Company Name:DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Info Phone Num:714-474-0400

Emergency Phone Num:800-424-9300 CHEMTREC

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (ME

K) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF THE RESPIRATORY
TRACT/HEADACHE/DIZZINESS/STAGGERING GAIT/UNCONSCIOUSNESS OR COMA.

===== First Aid Measures =====

First Aid:INHALED: MOVE FROM EXPOSURE. SKIN: REMOVE CONTAMINATED
CLOTHING BEFORE REUSE
. WASH W/SOAP & WATER. EYES: FLUSH W/CLEAN
LUKEWARM WATER FOR AT LEAST 15 MINS. INGESTED: DON'T INDUCE
VOMITING. DON'T GIVE ANYTHING BY MOUTH IF UNCONSCIOUS. GET MED
ATT.

===== Fire Fighting Measures =====

Flash Point:23F TCC
Lower Limits:1.5%
Upper Limits:11.5
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:SCBA & FULL PROTECTIVE CLOTHING SHOULD BE WORN
BY FIREFIGHTER
Unusual Fire/Explosion Hazard
:WATER COOL CLOSED CONTAINERS TO PREVENT
PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION WHEN EXPOSED TO HEAT

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NONESSENTIAL PERSONNEL. REMOVE
ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES).
VENTILATE AREA. CONTAIN & REMOVE WITH INERT ABSORBENT & NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID

STORING NEAR HIGH TEMPS, FIRE,
OPEN FLAMES, & SPARK SOURCES. STORE IN TIGHTLY CLOSED CONINERS.
STORE IN WELL VENTILATED AREAS.

Other Precautions:KEEP CONTAINERS TIGHT/UPRIGHT TO PREVENT LEAKAGE.
PREVENT PROLONGED/REPEATED BREATHING VAPOR/SPRAY MISTS. MAY CAUSE
AN ALLERC REACTION. DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN &
EYES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A RESPIRATOR APPROVED FOR USE WITH AN ORGANIC
VAPOR

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP AIR

Spec Gravity:1.2

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INSOLUBLE

Appearance and Odor:GRAY VISCOUS LIQUID WITH SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OR OPEN FLAME

Hazardous Decomposition Products:CO, CO2, NOX

===== Disposa

I Considerations =====

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE
W/FEDERAL, STATE, & LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY
CONTAINERS MUST BE HANDLED W/CARE DUE TO PRODUCT RESIDUE &
FLAMMABLE VAPOR. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatso
ever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.