

KINDT COLLINS CO -- MEASUR-WAX -- 9160-01-086-0143

===== Product Identification =====

Product ID:MEASUR-WAX

MSDS Date:11/07/1990

FSC:9160

NIIN:01-086-0143

MSDS Number: BGLCY

=== Responsible Party ===

Company Name:KINDT COLLINS CO

Address:12651 ELMWOOD AVENUE

City:CLEVELAND

State:OH

ZIP:44111-5911

Country:US

Info Phone Num:216-252-4122

Emergency Phone Num:216-252-4122

Preparer's Name:PAUL A. GUINN

CAGE:33629

=== Contractor Identification ===

Company Name:KINDT COLLINS CO

Address:12651 ELMWOOD AVENUE

Box:City:CLEVELAND

State:OH

ZIP:44111-5911

Country:US

Phone:216-252-4122/CHEMTREC 800-424-9300

CAGE:33629

===== Composition/Information on Ingredients =====

Ingred Name:PRECISE COMPOSITION IS PROPRIETARY INFORMATION AVAILABLE TO  
A PHYSICIAN IN EVENT OF A MEDICAL EMERGENCY.

RTECS #:9999999ZZ

Ingred Name:THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY THE OSHA HAZARD  
COM

MUNICIPATION STANDARD, CFR TITLE 29 1910.1200.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:TLV/TWA 2 MG/M3 FOR PARAFFIN WAX FUME

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MOLTEN WAX FUMES MAY BE SLIGHTLY  
IRRITATING TO EYES AND RESPIRATORY TRACT. MOLTEN WAX WILL CAUSE  
BURNS ON CONTACT WITH SKIN.

Explanation of Carcinogenicity:NOT LIS

TED

Effects of Overexposure:MOLTEN WAX FUMES MAY CAUSE SLIGHT IRRITATION TO EYES AND RESPIRATORY TRACT. MOLTEN WAX WILL CAUSE BURNS ON CONTACT WITH SKIN.

Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:FOR HOT WAX ON SKIN, COOL WITH WATER. APPLY ICE WATER OR PACKS TO BURNED AREA IF LESS THAN 10% OF THE BODY. DO NOT REMOVE WAX. GET MEDICAL ATTENTION. FOR EYE CONTACT, FLUSH WITH WATER FOR AT LEAST 15 MIN

UTES. GET MEDICAL ATTENTION. FOR INGESTION, CONSULT MEDICAL PERSONNEL. INHALATION: REMOVE VICTIM TO FRESH AIR. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:435F,224C

Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. COOL FIRE-EXPOSED CONTAINERS WITH WATER.

Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPM

ENT INCLUDING A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER. WAX MAY BURN ALTHOUGH NOT READILY IGNITABLE.

===== Accidental Release Measures =====

Spill Release Procedures:MAY BURN ALTHOUGH NOT READILY IGNITABLE. USE CAUTION WHEN CLEANING UP LARGE MOLTEN SPILLS. LARGE MOLTEN SPILL: SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE & CONTAIN. ALLOW WAX TO

COOL & REMOVE AS A SOLID. SMALL AMOUNTS SHOULD BE ALLOWED TO COOL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH HOT MATERIAL. MINIMIZE BREATHING OF VAPORS, FUMES OR MIST.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE, USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRAT

OR OR AN

AIR-PURIFYING RESPIRATOR FOR PARTICULATES. MINIMIZE BREATHING OF VAPORS, FUMES OR MIST.

Ventilation:NOT NORMALLY REQUIRED

Protective Gloves:AS APPROPRIATE TO PROTECT AGAINST HOTWAX

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING TO PROTECT SKIN AGAINST HOT MATERIAL.

Work Hygienic Practices:NOT SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

THIS PRODUCT MEETS FDA REQUIREMENTS FOR INDIRECT AND DIRECT FOOD USES.

=====

==== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>660F,>349C

Melt/Freeze Pt:M.P/F.P Text:168F,76C

Vapor Pres: