View NSN Online: https://aerobasegroup.es/nsn/6140-01-111-3745

## GATES ENERGY PRODUCTS AFFIL OF GATES RUBBER CO -- SEALED LEAD-ACID BATTERY --

6140-01-111-3745

============= Product Identification =================

Product ID:SEALED LEAD-ACID BATTERY

MSDS Date:03/01/1990

FSC:6140

NIIN:01-111-3745

MSDS Number: BGMHB === Responsible Party ===

Company Name: GATES ENERGY PRODUCTS AFFIL OF GATES RUBBER CO

Address:1050 S BROADWAY

Box:5887 City:DENVER State:CO ZIP:80217 Country:US

Info Ph one Num:303-744-5360

Emergency Phone Num:303-744-1911

CAGE:57053

=== Contractor Identification ===

Company Name: ENGINEERED ASSEMBLIES AND COMPONENTS CORP

Address:5289 CAPITAL BLVD

Box:City:RALEIGH

State:NC

ZIP:27604-2925 Country:US

Phone:919-790-9700

CAGE:0AC65

Company Name: GATES ENERGY PRODUCTS AFFIL OF GATES RUBBER CO

Address:1050 S BROADWAY

Box:5887 City:DENVER State:CO ZIP:80217 Country:US CAGE:57053

Company Name: TELEDYNE BROWN ENGINEERING

CAGE:14925

====== Composition/Information o

n Ingredients ========
Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: 69% OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB
Ingred Name:ACID ELECTROLYTE (PROPRIETARY) Fraction by Wt: 21% ACGIH TLV:1.0MG/M*3
Ingred Name:NON-HAZARDOUS MATERIALS Fraction by Wt: 10%
============ Hazards Identification =============
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Health Hazards Acute and Chro nic:MANUFACTURER STATES NO EXPOSURE. SEALED BATTERY IS AN ARTICLE. Effects of Overexposure:MANUFACTURER STATES NO EXPOSURE. SEALED BATTERY IS AN ARTICLE. Medical Cond Aggravated by Exposure:ECZEMA,DERMATITIS.  ===================================
First Aid:EYES/SKIN:FLUSH WITH LARGE AMOUNTS OF WATER.SEE DOCTOR IMMEDIATELY. INHALATION:REMOVE TO FRESH AIR. INGESTION:GIVE WATER OR MILK,THEN 2 OZ MILK OF MAGNESIA.SEE DOCTOR IMMEDIATELY. DO NOT IND UCE VOMITI NG.
======================================
Flash Point:NONE Extinguishing Media:MULTI-PURPOSE DRY CHEMICAL OR MULTI-PURPOSE CO*2. Fire Fighting Procedures:COOL BATTERY EXTERIOR TO PREVENT RUPTURE.THE ACID MISTS & VAPORS IN A FIRE ARE TOXIC & CORROSIVE. USE SCBA & PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:HYDROGEN GAS MAY BE PRODUCED AND MAY EXPLODE IF IGNITED. REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA.
========= Acci

dental Release Measures =========

Spill Release Procedures:PREVENT CONTACT WITH SPILLED MATERIAL. USE SODA ASH OR LIME TO NEUTRALIZE. FLUSH WITH LARGE AMOUNTS OF WATER AND PLACE IN ACID RESISTANCE CONTAINERS.WEAR ACID RESISTANT BOOTS,FACESHIELD,CHEMICAL SPLAS H GOGGLES & ACID RESISTANT GLOVES. Neutralizing Agent:SODA ASH (SODIUM CARBONATE),LIME (CALCIUM OXIDE).

========== Handling and Storage ===============

Handling and Storage Precautions:STORE IN A CLIMATE CONTROLLED WAREHOUSE TEMPERATURE NOT TO EXCEED 70F. Other Precautions:NONE.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE REQUIRED UNDER NORMAL USE.

Ventilation: MECHANICAL (GENERAL) VENTILATION.

Protective Gloves: VINYL COATED, PVC GLOVES.

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: SAFETY SHOES. EYE WASH & SAFETY SHOWER.

Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

**MANUFA** 

CTURER STATES NO EXPOSURE. SEALED BATTERY IS AN ARTICLE.

======== Physical/Chemical Properties ==========

HCC:C1

Appearance and Odor:SEALED LEAD-ACID BATTERY

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
NONE NOTED,BUT EXPECT COMBUSTIBLE MATLS,REDUCING
AGTS,METALS,CARBIDES,ORGANIC
MATL,CHLORATES,NITRATES,PICRATES&FULMINATE

Stability Condition to Avoid:AVOID SHORTING. USE ONLY APPROVED CHARGING ME

=======================================	Disposal Considerations	=======================================
Hazardous Decomposition	Products:HYDROGEN G	AS.
THODS.		

Waste Disposal Methods:DISPOSE OF IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabi

lity for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.