Product ID:EN ALKYD LUST QD YELLOW 33538 744310 MSDS Date:01/01/1987 FSC:8010 NIIN:01-122-1969 MSDS Number: BGMWV === Responsible Party === Company Name: PRATT AND LAMBERT, INC. Address:16116 E 13TH ST Box:2153 City:WICHITA State:KS ZIP:67201 Country:US CAGE:61196 === Contractor Identification === **Company Name: PRATT AND LAMBERT INC** Box:6027 City: **CLEVELAND** State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 Fraction by Wt: 20% OSHA PEL:2 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:ISOBUTYL ALCOHOL (SARA III) CAS:78-83-1 RTECS #:NP9625000 Fraction by Wt: 7% OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD CHRONATE Fraction by Wt: 5% ACGIH TLV:.05MG/CUMTR

Ingred Name:LEAD COMPOUNDS Fraction by Wt: 11% OSHA PEL:0.05 MG/M3 (PB) ACGIH TLV:0.15 MG/M3 (PB);8990

Effects of Overexposure:INGESTION:NAUSEA,VOMITING,ABDOMINAL PAIN;RESPIRATORY PA RALYSIS .EYE,SKIN IRRITATION;ORGAN DAMAGE

First Aid:INGESTION;INDUCE VOMITING.INHALATION:REMOVE TO FRESH AIR;RESTORE BREATHING.GET PHYSICIAN;KEEP WARM AND QUIET.EYES:15 MINUTE WATER FLUSH.SKIN:REMOVE CONTAMINATED CLOTHING.WASH SKIN WITH SOAP AND WATER. PHYSICIANS:TREAT FOR CONTROL OF SYMPTOMS.

Flash Point:20F,-7F

Extinguishing Media:CARBON DIOX

IDE, DRY CHEMICAL, ALCOHOL FOAM, POLYMER

FOAM

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS;WATER FOG ON CONTAINERS.

Unusual Fire/Explosion Hazard: FUMES FROM CONTAINERS MAY IGNITE FROM IGNITION SOURCES.CONTAINERS MAY EXPLODE FROM EXTREME HEAT.

Spill Release Procedures:REMOVE IGNITION SOURCES.CONTAIN WITH INERT MATERIAL.TRANSFER TO CLOSED CONTAINERS(METAL).PREVENT ENTRY INTO DRAINS,SEWERS,GROUND W

## ATERS.REMOVE SPILLAGE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.WEAR RESPIRATORS,EYE,AND SKIN PROTECTION.

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN ACCORDANCE WITH 0SHA CFR 1910.106. Other Precautions: KEEP CONTAINERS CLOSED. DO NOT BREATH FUMES, SANDING PARTICLES.AVOID SKIN CONTACT.GROUND AND BOND CONTAINERS.TO RECEIVING CONTAINER.DO NOT PUNCTURE EMPTY CONTAINER, EMPTY W TΗ PRESSURE Respiratory Protection: REFER TO OSHA 29 CFR 1910.1025.N10SH10SHA 29 CFR 1910.134. Ventilation: REFER TO OSHA 29 CFR 1910.1025.EXHAUST DECOMPOSED PRODUCTS. Protective Gloves:SOLVENT RESIST. Eye Protection: SHIELDED GOGGLES, GLASSES. Other Protective Equipment: EYEWASH, SAFETY SHOWER. REFER TO OSHA LEAD STANDARD. Supplemental Safety and Health Boiling Pt:B.P. Text:190F,88C Vapor Density:>AIR Evaporation Rate & amp; Reference: SLOWER THAN ETHER Percent Volatiles by Volume:62 Stability Indicator/Materials to Avoid:YES STRONG ACIDS, OXIDIZERS, ALKALINES. Stability Condition to Avoid: IGNITION SOURCES, EXCESSIVE HEAT. Hazardous Decomposition Products:C01C0\*2,LEAD OXIDES,SMOKE CAUSED BY IGNITION.

Wast

e Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.INCINERATE IN EPA APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizin g this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.