View NSN Online: https://aerobasegroup.es/nsn/6750-01-129-0866

Product ID:180 3998, MICROFILM CLEARING BATH & REPL MSDS Date:08/18/1982 FSC:6750 NIIN:01-129-0866 **MSDS Number: BGNDN** === Responsible Party === Company Name: EASTMAN KODAK CO. Address:343 STATE STREET **City:ROCHESTER** State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 **Emergency Ph** one Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:POTASSIUM SULFITE CAS:10117-38-1 Fraction by Wt: 15-20% Other REC Limits:NONE ESTABLISHED

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 75-80% Other RE C Limits:NONE ESTABLISHED

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:MSDS FM MFR STATES THAT EFFECTS OF OVEREXPOSURE ARE OF LOW HAZARD TO HEALTH.

First Aid:PER MFR MSDS,"NONE INDICATED.";HOWEVER,FLUSH W/LG AMT OF WATER IN CASE OF SKIN/EYE CONTACT.GET MED ATTN IF NEEDED OR SYMPTOMS OCCUR.

Flash Point:NONE Extinguishing Media:CO*2,FOAM,DRY CHEM

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS, PROVIDE VENTILATION/SAFETY EQUIPMENT IF NECESSARY.DIKE LG SPILL & PUMP INTO COVERED CONTNRS; ABSORB SM SPILL W/ABSORBING MATL & PLACE IN SAME CONTNR; MFR SUGGESTS FLUSH DOWN TO SEWER W/LG AMT OF H*20 IAW

EXISTINGREGS.

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions: AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF PRODUCT: 8.4

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE REQD IN NORMAL CONDIT

IONS. Ventilation:MECHANICAL(GEN) IF NEEDED Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES. Supplemental Safety and Health MSDS FM MFR DATED:08/18/82

HCC:N1 Boiling Pt:B.P. Text:>212F/>100C Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.22 pH:8.4 Solubility in Water:COMPLETE Appearance and Odor:CLEAR,ODORLESS LIQUID Percent Volatiles by Volume:75

Stability Indicator/Materials to Avoid:YES PER MFR,MINERAL ACIDS Hazardous Decomposition Products:PER MFR,SULFURDIOXIDE

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.DISPOSE IN FULL COMPLIANCE W/FEDERAL,STATE & LOCAL REGULATIONS;MFR RECOMMENDS TO FLUSH DOWN TO SEWER W COPIOUS AMT H*20.STATE & LOCAL EFFLUENT LAWS TAKE PRE CEDENCE.

Dis

claimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.