

INLAND PACKAGING,INC -- 340 HEAT SINK,COMPOUND -- 6850-01-137-8525

===== Product Identification =====

Product ID:340 HEAT SINK,COMPOUND

MSDS Date:01/01/1987

FSC:6850

NIIN:01-137-8525

MSDS Number: BGNNW

=== Responsible Party ===

Company Name:INLAND PACKAGING,INC

Emergency Phone Num:502 737 6757

CAGE:66172

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phon

e:502-737-6757

CAGE:66172

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYLSILOXANE(CAS#63148-62-9)(PRIMARY COMPONENT)

CAS:9016-00-6

RTECS #:TQ2690000

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

OSHA PEL:15MG/M3 TDUST/5 FUME

ACGIH TLV:10MG/M3 TDUST; 9293

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN IRRITANT.

===== First Aid Measures =====

Fi

rst Aid:EYE:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN.
IRRITATION DOES NOT INVOLVE CORNEA.AND SHOULD SUBSIDE WITHIN HOURS.
SKIN:WASH W/SOAP & WATER. INGEST:INDUCE VOMITING AS QUICKLY AS
POSSIBLE.SEEK MED ICAL ASSITANCE.

===== Fire Fighting Measures =====

Flash Point:>648F/342C(CC)
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP
Unusual Fire/Explosion Hazard:COMBUSTIBLES

=====

= Accidental Release Measures =====

Spill Release Procedures:SCRAPE PRODUCT UP FROM CONTAMINATED AREA;
REMOVING RESIDUE WITH A SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE IN ORIGINAL
UNOPENED CONTAINERS BETWEEN 41-77F.WASH HANDS THOROUGHLY AFTER
HANDLING. DO NOT RUN EYES W/SOILED HANDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protect
ion:NOT NORMALLY
Ventilation:YES
Protective Gloves:YES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE BATH.
Supplemental Safety and Health
MSDS DATED 1-24-86.

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:2.3
Solubility in Water:INSOLUBLE
Appearance and Odor:WHITE OPAQUE COLOR, SLIGHT ODOR,PASTE.
Percent Volatiles by Volume:1.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YE

S
MINERAL ACID, STRONG BASE,OXIDIZING MATL,OXYGEN UNDER PRESS.
Stability Condition to Avoid:AVOID OPEN FLAME,ELECTRIC ARC,IGNITION
SOURCES.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for
use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.