

DOW CORNING CORP. -- 1204 PRIMER -- 8040-01-155-7545

===== Product Identification =====

Product ID:1204 PRIMER

MSDS Date:01/01/1987

FSC:8040

NIIN:01-155-7545

MSDS Number: BGPHD

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contrac

tor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 65%

OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 2.0%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ORGANOSILICATE
Fraction by Wt: 5.0%
ACGIH TLV:5 PPM (MFR)

===== Hazards Identification =====

Ef
fects of Overexposure:EYE:IRRIT,DAMAGE CORNEA. SKN:SL
IRRIT;INHL:IRRIT,DIZZ. INGEST: NOT STATED.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/AMPLE WATER. SKIN: WIPE & FLUSH W/AMPLE WATER.
INHL: REMOVE TO FRESH AIR. CALL PHYS. INGEST: CALL PHYS.

===== Fire Fighting Measures =====

Flash Point:59F/15C CC
Extinguishing Media:WATER FOG, CO*2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:USE SCBA & PROTECT CLOTHIN

G WHEN FIGHTING
FIRES

Unusual Fire/Explosion Hazard:NONE STATED.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. COLLECT SPILLAGE
W/ABSORBENT. WEAR SCBA, PROTECT CLOTHING.

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE LIQUID. AVOID XS HEAT,
FLAME, SPARKS. KEEP CONTAINERS CLOSED. STORE IN COOL, VENTILATED
AREA.

Other Precautions:NONE STATED

.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CCR AS REQ'D.
Ventilation:LOCAL OR MECHANICAL RECOMMENDED
Protective Gloves:NONE STATED
Eye Protection:GOGGLES, SAFETY
Supplemental Safety and Health
ENTRY PER OSHA MSDS DTD 20SEP85.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:210F/99C
Vapor Pres:25
Vapor Density:>1
Spec Gravity:0.8
Evaporation Rate & Reference: