

DYNAMOLD, INC. -- DYNACHEK MR-502K -- 6850-01-163-0276

===== Product Identification =====

Product ID:DYNACHEK MR-502K

MSDS Date:07/01/1989

FSC:6850

NIIN:01-163-0276

Kit Part:Y

MSDS Number: GPLX

==== Responsible Party ===

Company Name:DYNAMOLD, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Country:US

Info Phone Num:817-335-0863

Emergency Phone Num:817-335-0862

CAGE:3025

6

==== Contractor Identification ===

Company Name:DYNAMOLD SOLVENTS, INC.

Address:2905 SHAMROCK AVE

Box:9617

City:FORT WORTH

State:TX

ZIP:76107

Country:US

Phone:817-335-0862

CAGE:30256

===== Composition/Information on Ingredients =====

Ingred Name:NO HAZARD INGREDIENTS STATED BY MANUFACTURERS

===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:NO DATA AVAILABL

E;MAY CAUSE

IRRITATION OF SKIN & EYES. CHRONIC:NO DATA AVAILABLE.

Effects of Overexposure:EYES:MAY CAUSE IRRITATION;SKIN:NOT KNOWN TO

MFR;INHALATION/INGESTION:NOT KNOWN TO MANUFACTURER.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP & H<sup>2</sup>O. EYES:FLUSH W. H<sup>2</sup>O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:265F,129C

Lower Limits:NON EXPLOS.

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire

/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.

EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED

AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:NOT KNOWN

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:MECHANICAL (GENERAL)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Supplemental Safety and Health

===== Physical/Chemical Properties

=====

HCC:N1

Boiling Pt:B.P. Text:>300F/149C

Vapor Pres:1.0

Vapor Density:NEGLIGIBLE

Spec Gravity:1.0

Evaporation Rate & Reference:0.8 (WATER=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:GRAY, SLIGHT ODOR

Percent Volatiles by Volume: