

XEROX CORPORATION -- 6R301;DRY INK/TONER -- 6850-01-165-5409
===== Product Identification =====

Product ID:6R301;DRY INK/TONER
MSDS Date:04/10/1990
FSC:6850
NIIN:01-165-5409
MSDS Number: BGPND
=== Responsible Party ===
Company Name:XEROX CORPORATION
Address:100 CLINTON AVE SOUTH
Box:1540
City:ROCHESTER
State:NY
ZIP:14644-1877
Country:US
Info Phone Num:800-828-6571
Emergency Phone Num:716-422-2177
Preparer's Name:MSDS# A-0023
CAGE:26921
=== Contractor Identification ===
Company Name:XEROX CORPORATION
Address:100 CLINTON AVE SOUTH
Box:City:ROCHESTER
State:NY
ZIP:14644-1877
Country:US
Phone:800-828-6571/716-422-2177
CAGE:26921

===== Composition/Information on Ingredients =====

Ingred Name:STYRENE ACRYLATE COPOLYMER
CAS:25213-39-2
Fraction by Wt: >90%

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 5-10%
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:QUATERNARY AMMONIUM SALT (TRADE SECRET)
Fraction

by Wt: 10G/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS PRACTICALLY
NON-TOXIC,NON-SENSITIZING,MINIMALLY IRRITATING,NON-MUTAGENIC.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:MINIMAL RESPIRATORY TRACT IRRITATION MAY OCCUR
AS WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC D
UST.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING
RESPIRATORY AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER; SKIN:WASH WITH SOAP & WATER;
INHALATION:REMOVE FROM EXPOSURE; INGESTION:DRINK SEVERAL GLASSES OF
WATER.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:WATER,FOAM,DRY CHEMICAL,CARBON DIOXIDE.
Fire
Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.AVOID INHALATION OF SMOKE.
Unusual Fire/Explosion Hazard:THIS POWDER CAN FORM EXPLOSIVE MIXTURES
WITH AIR.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR SWEEP UP SPILLED TONER AND TRANSFER
TO A SEALABLE CONTAINER FOR DISPOSAL.SWEEP SLOWLY TO AVOID
DUSTING,OR USE A VACUUM WITH A MOTOR RATED FOR DUST.THE HOSE ON THE
VACUUM SHOULD
BE BONDED TO AVOID STATIC.WASH AREA W/SOAP AND
WATER.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID INHALING DUST.
Other Precautions:NONE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.
Ventilation:NORMAL ROOM VENTILATION. (LOCAL EXHAUST IF HANDLING PRODUCT
IN BULK.)
Protective Gloves:NONE NORMALLY REQUIRED.
Eye Protection:NOT

NEEDED IN NORMAL SERVICE.

Other Protective Equipment:GOGGLES & RESPIRATORS MAY BE REQD IN BULK
PROCESS FACILITIES

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.USE REASONABLE
CARE.

Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity: 1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK POWDER,FAINT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Mater

ials to Avoid:YES

NONE

Stability Condition to Avoid:DUST+SOURCES OF IGNITION.

Hazardous Decomposition Products:PRODUCTS OF COMBUSTION MAY BE TOXIC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL REGULATIONS.INCINERATE ONLY IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defe

nse. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.