

D-A LUBRICANT COMPANY,INC. -- D-A WIRE ROPER SAVER -- 9150-01-179-0228

===== Product Identification =====

Product ID:D-A WIRE ROPER SAVER

MSDS Date:03/15/1989

FSC:9150

NIIN:01-179-0228

MSDS Number: BGPWL

=== Responsible Party ===

Company Name:D-A LUBRICANT COMPANY,INC.

Address:1340 W. 29TH STREET

City:INDIANAPOLIS

State:IN

ZIP:46208

Country:US

Info Phone Num:216-391-8300

Emergency Phone Num:317-923-5321

CAGE:30719

=== Contractor Identification ===

Company Name

:D-A LUBRICANT CO INC SUB OF PREMIER INDUSTRIAL

Address:1340 W 29TH ST

Box:City:INDIANAPOLIS

State:IN

ZIP:46208-4943

Country:US

Phone:317-923-5321/216-391-8300 OTHER HRS

CAGE:30719

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM OIL

CAS:69029-75-0

Fraction by Wt: 5-10%

OSHA PEL:5MG/CUM,AS OIL MIST

ACGIH TLV:5MG/CUM,AS OIL MIST

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 15-40%

OSHA PE

L:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:LEAD NAPHTHENE
CAS:61790-14-5
RTECS #:QK9150000
Fraction by Wt: 3-7%
Other REC Limits:NOT SPECIFIED
OSHA PEL:50 MG/CUM AS LEAD
ACGIH TLV:0.15MG/CUM,AS LEAD

Ingred Name:ASPHALT (PETROLEUM)
CAS:8052-42-4
RTECS #:CI9900000
Fraction by Wt: 40-70%
ACGIH TLV:5 MG/M3; (FUME);9192

===== Hazards Identification =====

Routes of Entry: Inhal
ation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF
EYES,SKIN,RESPIRATORY OR G.I. TRACT,NAUSEA,CRAMPS,DIARRHEA AND
OTHER GASTROINTESTINAL DISORDERS.CHRONIC:CNS EFFECTS,BLOOD,LIVER
AND KIDNEY EFFECTS OR DAMAGE TO LUNG,KIDNEY,STOMACH AND/OR
PRODUCTIVE SYSTEM.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE
MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>370F/188C
Autoignition Temp:Autoignition Temp Text:>500
Extinguishing Media:DRY CHEMICAL,CO*2,FOAM,WATERFOG
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA,IN CONFINED
SPACE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE ON HEATING

===== Accidental Release Measures =====

=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:RECOVER FREE LIQUID;USE SUITABLE INERT ABSORBENT MATERIAL AND COLLECT FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES AND SPARKS.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES.DO NOT BREATHE VAPORS.DO NOT EAT,DRINK OR SMOKE IN WORK AREA.

===== Expo
sure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORG.VAPORS IF ABOVE TLV.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:165F/74C

Melt/Freez

e Pt:M.P/F.P Text:-20F/-4C

Vapor Pres:100

Vapor Density:4.5

Spec Gravity:1.2

Evaporation Rate & Reference: