BATTENFELD GREASE & OIL CORPORATION OF NEW YORK -- BATAM S-830-RR 9150-01-197-7691

Product ID:BATAM S-830-RR MSDS Date:01/01/1985 FSC:9150 NIIN:01-197-7691 **MSDS Number: BGQJS** === Responsible Party === Company Name: BATTENFELD GREASE & OIL CORPORATION OF NEW YORK Emergency Phone Num:(716) 695-2100 CAGE:EO110 === Contractor Identification === Company Name: BATTENFELD GREASE AND OIL CORP OF NEW YORK INC Address:1174 ERIE AVE Bo x:728 **City:NORTH TONAWANDA** State:NY ZIP:14120-3036 Country:US Phone:716-695-2100 CAGE:60226 Company Name: BATTENFELD GREASE AND OIL CORP OF NEW YORK INC Address:1174 ERIE AVE Box:728 **City:NORTH TONAWANDA** State:NY ZIP:14120-3036 Country:US Phone:716-695-2100 CAGE:EO110

Ingred Name:LITHIUM 12 HYDROXYSTEARATE; CAS #7620-77-1 PER MFR & EPA-TSCA,INITIAL INVENTORY Fraction by Wt: 10.0%

Ingred Name: MINERAL OIL (EXPOSURE REGULATE

D AS 'OIL MIST') CAS:8012-95-1 RTECS #:PY8030000 Fraction by Wt: 33.0% OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:POLYALPHAOLEFIN FLUID; CAS #8037-01-4 PER MFR & EPA-TSCA,INITL INVENTORY. Fraction by Wt: 50.0%

Ingred Name:PHOSPHATE ESTER; CAS #68025-51-4 PER MFR & EPA-TSCA INITL INVENTORY Fraction by Wt: 05.0%

Ingred Name:ZINC DIAMYLDITHIOCARBAMATE; CAS #15337-18-5,PER MFR & EPA-TSCA INITL INVENTORY Fraction by Wt: 02.0%

======= Hazards Identificat

Effects of Overexposure: MAY CAUSE SKIN/EYE MILD IRRITATION.

First Aid:SKIN:WASH/FLUSH WITH SOAP & WATER.REMOVE & LAUNDER CONTAMINATED CLOTHING;EYES:FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN.GET MEDICAL ATTN;INGESTION: DO NOT INDUCE VOMITING.GIVE PLENTY OF WATER.GET MEDICAL ATTENTION.

Flash Point:400F-COC/(D-92)

Autoignition Temp:Autoignition Temp Text:460F Extinguishing Media:WATER FOG,CO\*2, DRY CHEM, FOAM, EARTH OR SAND Fire Fighting Procedures:PER MFR,WATER MAY CAUSE FROTHING Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: ELIM IGNITION SOURCES. USE PROTECTV EQUIP SUCH AS GLOVES & SAFETY GOGGLES. ABSORB WITH SAND OR INERT MATERIAL. SWEEP OR SCOOP UP AND PLACE IN SALVAGE TANK. KEEP COVERED PENDING DISPOSAL.

===

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS AWAY FROM HEAT/OPEN FLAMES. Other Precautions:NONE KNOWN

Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:NORMAL ROOM VENTILATION. Protective Gloves:PVC/NEOPRENE Eye Protection:AS REQUIRED Other Protective Equipment:NONE NORMALLY REQUIRED Supplemental Safety and Health MSDS FM MFR UN DATED.MFR STATED 5/28/85 FORMULATION DEVELOPED IAW REV E OF MIL-G-10924; MFR PRODUCT CODE #10,791.

HCC:V6 Boiling Pt:B.P. Text:700F Spec Gravity:0.88 Solubility in Water:NEGLIGIBLE Appearance and Odor:AMBER SMOOTH GREASE-SLIGHTLY SWEET

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE IF INCOMPLETE COMBUSTION

Waste Disposal Methods: INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.