

FISKE BROS.REFINING CO. -- LUBRIPLATE FMO-AW SERIES -- 9150-01-237-7980

=====
Product Identification
=====

Product ID:LUBRIPLATE FMO-AW SERIES

MSDS Date:03/01/1987

FSC:9150

NIIN:01-237-7980

MSDS Number: BGRDK

=== Responsible Party ===

Company Name:FISKE BROS.REFINING CO.

Address:129 LOCKWOOD ST.

City:NEWARK

State:NJ

ZIP:07105-4720

Info Phone Num:201-589-9510

Emergency Phone Num:201-589-9150

Prepar

er's Name:ROBERT J. SIBILIA

CAGE:NO273

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROS.REFINING CO.

Address:129 LOCKWOOD ST.

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Phone:201-589-9510

CAGE:NO273

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3,STEL 10

Ingred Name:ADD

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT AND HAS A
LOW ORAL TOXICITY. HOWEVER,MINUTE AMOUNTS ASPIRATED INTO THE LUNGS
MAY CAUSE MILD TO SEVERE PULMONARY INJURY.
Effects of Overexposure:EYE:IRRITATION. SKIN:POSSIBLE IRRITATION.
INHALED:RESPIRATORY IRRITATION,BREATHING
DIFFICULTY.
INGESTED:POSSIBLE G/I IRRITATION.
Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN OR UNTIL IRRITATION SUBSIDES.
SKIN:REMOVE CONTAMINATED CLOTHING,WASH WITH SOAP & WATER. LAUNDER
CLOTHING BEFORE REUSE. INHALED:DUE TO LOW VAPOR PRESSURE,VAPORS ARE
PROBLEM ONLY IF HEATED. REMOVE FROM EXPOSURE TOVAPORS OR MIST. IF
IRRITATION PERSISTS,GET MEDICAL CARE. INGESTION:DO NOT INDUCE
VOMITING. GET PROMPT MEDICAL CARE.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:340F-425F
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER FOG
Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. WEAR SELF
CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:EMPTY CONTAINERS MAY CONTAIN VAPORS
MAKING THEM EXPLOSION HAZARDS.

=====
===== Accidental
Release Measures =====

Spill Release Procedures:ABSORB WITH APPROPRIATE MATERIAL
(RAGS,PAPER,VERMICULITE,ETC.). STORE FOR DISPOSAL. CLEAN WITH
SUITABLE PETROLEUM SOLVENT. TAKE FIRE PRECAUTIONS APPROPRIATE FOR
THE SOLVENT.
Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A LOW FIRE
RISK AREA.

=====
===== Exposure Controls/Personal Protection =====

piratory Protection:NONE NORMALLY NEEDED. USE NIOSH CARTRIDGE
RESPIRATOR FOR OIL MIST OR VAPOR WHEN EXPOSED ABOVE PEL/TLV.

Ventilation:NORMAL ROOM VENTILATION NORMALLY SUFFICIENT.

Protective Gloves:OIL RESISTANT TO MINIMIZE CONTACT.

Eye Protection:SAFETY GLASSES:GOGGLES IF SPLASH LIKELY

Other Protective Equipment:OIL RESISTANT APRON WHEN SPLASHES ARE
LIKELY.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID ANY
UNNECESSARY CONTACT.

Supplemental Safety and Health

==

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F/288C

Vapor Pres:5

Spec Gravity:0.86-0.89

Evaporation Rate & Reference: