

EXXON CHEMICAL AMERICAS, DIV OF EXXON CHEMICAL CO -- GASOLINE, UNLEADED (ALL GRADES) -- 9130-00-148-7103

===== Product Identification =====

Product ID:GASOLINE, UNLEADED (ALL GRADES)

MSDS Date:12/02/1991

FSC:9130

NIIN:00-148-7103

MSDS Number: BGWLJ

=== Responsible Party ===

Company Name:EXXON CHEMICAL AMERICAS, DIV OF EXXON CHEMICAL CO

Address:800 BELL STREET

Box:3272

City:HOUSTON

State:TX

ZIP:77001

Country:US

Info Phone Num:713-870-6885 (HEALTH/SAFETY)

Emerge

ncy Phone Num:713-870-6000

CAGE:72190

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXONMOBIL CHEMICAL CO, DIV OF EXXON MOBILCORP.

Address:13501 KATY FWY

Box:3272

City:HOUSTON

State:TX

ZIP:77253-3272

Country:US

Phone:281-870-6000 / 800-726-2015

CAGE:72190

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM), LI

GHT CATALYTIC CRACKED  
CAS:64741-55-5  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA (PETROLEUM), HEAVY CATALYTIC CRACKED  
CAS:64741-54-4  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, FULL RANGE REFORMED  
CAS:68919-37-9  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT ESTABLISHED.  
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:NAPHTHA (PETROLEUM), FULL-RANGE ALKYLATE  
CAS:64741-64-6  
Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA (PETROLEUM), SWEETENED  
CAS:64741-87-3  
Other REC Limits  
:NONE RECOMMENDED

Ingred Name:BUTANE  
CAS:106-97-8  
RTECS #:EJ4200000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:800 PPM  
ACGIH TLV:800 PPM; 9293

Ingred Name:ADDITIVES  
Other REC Limits:NONE RECOMMENDED

Ingred Name:EXXON LISTED THE FOLLOWING CHEMICALS FOR SARA III  
REPORTING. THIS PRODUCT MAY CONTAIN THE APPROXIMATE AMOUNTS  
INDICATED.  
RTECS #:9999999ZZ  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BENZENE (SARA III)  
CAS:71-43-2  
RTECS #:CY1400000  
Fraction by Wt: 4.9%  
Other REC Limits:NONE

RECOMMENDED  
OSHA PEL:1PPM/5STEL;1910.1028  
ACGIH TLV:10 PPM; A2; 9293  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:CUMENE (SARA III)  
CAS:98-82-8  
RTECS #:GR8575000  
Fraction by Wt: 0.3%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:CYCLOHEXANE (SARA III)  
CAS:110-82-7  
RTECS #:GU6300000  
Fraction by Wt: 0.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM, 9293  
EPA Rpt Qty:1000 LBS  
DOT  
Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: 2.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/125 STEL  
ACGIH TLV:100 PPM/125STEL 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)  
CAS:1634-04-4  
RTECS #:KN5250000  
Fraction by Wt: 6.0%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:NAPHTHALENE (SARA III)  
CAS:91-20-3  
RTECS #:QJ0525000  
Fraction by Wt: 0.7%

Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 PPM/15 STEL  
ACGIH TLV:10 PPM/15 STEL; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 16%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5G/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:INHALATION: MODERATE RISK OF VAPOR  
INTOXICATION. MAJOR RISK IS ENCLOSED SPACES WITH POOR VENTILATION.  
SKIN: DEFATTING WITH DRYING AND CRACKING CAN LEAD TO D  
ERMATITIS AND  
SECONDARY INFECTION. EYE: IRRI TANT. INGESTION: BURNING OF MOUTH  
AND UPPER GI TRACT, VOMITING AND DIARRHEA. PROLONGED OR REPEATED  
CONTACT: DERMATITIS.  
Explanation of Carcinogenicity:CONTAINS B [71-43-2] WHICH IS  
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.  
Effects of Overexposure:INHALATION MAY CAUSE EUPHORIA, LUNG IRRITATION  
AND EDEMA, HEADACHE, DIZZINESS, DROWSINESS, CONVULSIONS, COMA,  
CYANOSIS, GENERALIZED DEPRESSION. INGESTION MAY CAUSE

## GENERAL

DEPRESSION, SEDATION, RESPIRATORY DEPRESSION, COMA.

Medical Condition Aggravated by Exposure: MAY AGGRAVATE PRE-EXISTING

DERMATITIS, RESPIRATORY ILLNESS, OR OTHER CONDITIONS WHICH HAVE THE SAME SYMPTOMS OR EFFECTS AS STATED ABOVE.

### ===== First Aid Measures =====

First Aid: EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH

FRESH AIR. FOR RESPIRATORY

DISTRESS, GIVE AIR, OXYGEN, OR CPR IF NECESSARY. INGESTION: DO NOT INDUCE VOMITING. KEEP HEAD BELOW HIPS IF VOMITING OCCURS TO PREVENT ASPIRATION INTO LUNGS. GET MEDICAL ATTENTION IF REQUIRED IN ALL CASES.

### ===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: -37.8C, -36.F

Lower Limits: 1.4

Upper Limits: 7.6

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:

WATER MAY BE INEFFECTIVE ON FLAMES, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL. LARGE FIRES, SUCH AS TANK FIRES, SHOULD BE FOUGHT WITH CAUTION.

Unusual Fire/Explosion Hazard: HIGHLY VOLATILE MATERIAL. FLOWING GASOLINE CAN BE IGNITED BY SELF-GENERATED STATIC ELECTRICITY. VAPORS MAY TRAVEL ALONG THE GROUND TO A REMOTE IGNITION SOURCE.

### ===== Accidental Release Measures =====

Spill Release Procedures: SMALL: TAKE UP WITH NON COMBUSTIBLE ABSORBENT

SUCH AS FULLER'S EARTH OR SAND. PLACE INTO CONTAINERS FOR LATER DISPOSAL. LARGE: CONTAIN SPILL IN EARTHEN DIKES FOR LATER RECOVERY. CONTROL IGNITION SOURCES AROUND SPILL AREA. REPORT SPILLS AS REQUIRED.

### ===== Handling and Storage =====

Handling and Storage Precautions: AVOID STATIC IGNITION HAZARD WHEN TRANSFERRING MATERIAL. KEEP CONTAINERS CLOSED AND AWAY FROM HEAT & IGNITION SOURCES! DO NOT USE AS CLEANING AGENT.

Other Precautions:

utions:EMPTY CONTAINERS RETAIN SOME LIQUID/VAPOR RESIDUES;  
HAZARD PRECAUTIONS MUST BE OBSERVED WHEN HANDLING EMPTIES. KEEP OUT  
OF REACH OF CHILDREN! DO NOT USE ANY HYDROCARBON FUEL IN SPACES  
WITHOUT ADEQUATE VENTILATION. USE ONLY AS A FUEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR,  
SUPPLIED AIR, OR SELF-CONTAINED BREATHING APPARATUS (SCBA) MUST BE  
USED WHEN VAPOR CONCENTRATIONS  
EXCEED THE OCCUPATIONAL EXPOSURE  
LIMITS.

Ventilation:USE ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATIONS OF  
THIS MATERIAL BELOW THE OCCUPATIONAL EXPOSURE LIMITS.

Protective Gloves:WEAR OIL IMPERVIOUS (EG: NITRILE) GLOVES

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:OIL IMPERVIOUS INDUSTRIAL WORK CLOTHING TO  
MINIMIZE SKIN CONTACT. EYE BATH AND SAFETY SHOWER RECOMMENDED.

Work Hygienic Practices:USE GOOD PERSONAL HYGIENE. USE WATERLESS HAND  
C

LEANER TO WASH EXPOSED SKIN. LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.

Supplemental Safety and Health

THE VARIABLE COMPOSITION MAKES IT IMPOSSIBLE TO SET A SPECIFIC EXPOSURE  
LIMIT FOR ALL COMPOSITIONS OF THIS MATERIAL. SPECIFIC EXPOSURE  
LIMITS FOR POTENTIAL COMPONENTS SUCH AS BENZENE SHOULD BE APPLIED  
BASED ON AIR MONITORING TO ASSURE EMPLOYEES ARE NOT EXPOSED TO  
EXCESSIVE VAPOR LEVELS OF COMPONENTS.

===== Physical/Chemical Properties =====

HC  
C:F1  
Boiling Pt:>21.1C, 70.F  
Melt/Freeze Pt:=-37.8C, -36.F  
Vapor Pres:400  
Vapor Density:5  
Spec Gravity:0.74  
pH:7  
Evaporation Rate & Reference:10.5(N-BUTYL ACETATE=1)  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:CLEAR LIQUID WITH GASOLINE ODOR.  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES  
OF

## IGNITION

Hazardous Decomposition Products: BURNING OR EXCESSIVE HEATING MAY PRODUCE CARBON MONOXIDE AND OTHER HARMFUL GASES/VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods: IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE IF THE MATERIAL IS A HAZARDOUS WASTE AT THE TIME OF DISPOSAL. CHECK BEFORE DISPOSING TO BE SURE YOU ARE IN COMPLIANCE WITH ALL APPLICABLE LAWS AND REGULATIONS. CHEMTREC/RCRA EMER. NO.: 800-424-9346

## Discla

imer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.