

MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED --  
EXTINGUISHER,FIRE,VAPORIZING LIQUID -- 4210-00-435-9415

===== Product Identification =====

Product ID:EXTINGUISHER,FIRE,VAPORIZING LIQUID  
MSDS Date:07/12/1989  
FSC:4210  
NIIN:00-435-9415  
MSDS Number: BGXJX  
=== Responsible Party ===  
Company Name:MFR UNKNOWN/DEFENSE CONSTRUCTION S. CTR PROCURED  
Box:3990  
City:COLUMBUS  
State:OH  
ZIP:43216-5000  
Country:US  
Info Phone Num:614-238-3131  
Preparer's Name:DGSC-SLM/DOD-HMIS  
CAGE:JO772  
=== Contractor Identification ===  
Company Name:DEFENSE CONSTRUCTION SUPPLY CENTER  
Address:NONE  
Box:3990  
City:COLUMBUS  
State:OH  
ZIP:43215-5000  
Country:US  
Phone:614-238-3131  
CAGE:16236  
Company Name:MFR UNKNOWN/DEFENSE INDUSTRIAL SUPPLY CTR PROCURED  
Address:700 ROBBINS AVENUE  
Box:3990  
City:PHILADELPHIA  
State:PA  
ZIP:19111-5096  
Country:US  
Phone:215-697-2000  
CAGE:JO772

===== Composition/Information on Ingredients =====

Ingred Name:TRIFLUOROBROMOMETHANE (HALON 1301) (SA

RA III)  
CAS:75-63-8  
RTECS #:PA5425000  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM; 9192  
Ozone Depleting Chemical:1

===== Hazards Identification =====

LD50 LC50 Mixture:LC50=416 GM/CUM (RAT)  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: ASPHYXIAN'T CNS' & PULMONARY  
EFFECTS. SKIN IRRITANT. CHRONIC:NONE KNOWN.  
Effects of Overexposure:INHAL:DIZZINESS,DISORIENTATION,I  
MPAIRED  
COORDINATION, NARCOSIS, NAUSEA, OR  
VOMITING,LIGHT-HEADEDNESS,GIDDINESS,BREATH SHORTNESS. CARDIAC  
ARRHYTHMIA W/ UNCONSCIOUSNESS OR EVEN DEATH IH HI-CONC W/LONG E  
XPOSURE; SKIN/EYES: CONTACT W/LIQUID CAN CAUSE FROSTBITE, OR SKIN  
IRRITATION.  
Medical Cond Aggravated by Exposure:CARDIAC PROBLEMS. (PRODUCT IS AN  
ASPHYXIAN'T & CAN INDUCE CARDIAC MUSCLE SENSITIZATION TO CIRCULATE  
EPINEPHRINE-LIKE COMPOUNDS).

===== First Aid Measures =====

=====

First Aid:INHAL:REMOVE TO FRESH AIR-GET MED ATTN & GIVE O\*2/CPR AS  
REQUIRED FOR SITUATION @ HAND; DONOT GIVE EPINEPHRINE OR SIMILIAR  
DRUNS AS CATERCOLAMINES INCREASE RISK OF ELICITINH CARDIAC  
DYSRYTHMIAS. EYES/ SKIN:FLUSH W/WATER-TREAT FOR FROSTBITE W/MEDICAL  
ATTN.; INGEST:NOT LIKELY TO OCCUR.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:MATERIAL IS A FIRE EXTINGUISHANT & IS  
NON-FLAMMABLE. USE MEDIA APPR  
OPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:USE SCBA' WHEN FIGHTING FIRES WHERE CHEMICALS  
ARE INVOLVED.SCBA MAY BE NEEDED IF HALON-1301 CONTAINER RUPTURES OR  
RELEASES MATERIAL IN HEAT OF FIRE.  
Unusual Fire/Explosion Hazard:IN HEAT OF FIRE, HALON-1301 CONTAINER  
EXPOSED TO INTENSE HEAT OF FIRE MAY RUPTURE & MATERIAL COMPOSITION  
MAY OCCUR.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA OF UNNEEDED PERSONNEL, VE

NTILATE

AREA ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MIGHT COLLECT. COOL  
OR REMOVE HOT METAL SURFACES OR SOURCES OF NON-EXTINGUISHED FLAMES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE & HANDLE AS A LIQUIFIED  
COMPRESSED GAS IN DOT' APPROVED PRESSURE VESSELS AWAY FROM  
HI-TEMPERATURES.

Other Precautions:AVOID UNNECESSARY EXPOSURE TO HALON 1301! IN  
EMERGENCY, EXPOSURE SHOULD BE LIMITED TO: 0-7%, 15 MIN; 7-15%, 1  
MIN; 10-15%, 30 SEC; & FOR >15%, PREVENT EXPOSURE. SMALL CONC(5%)  
OF HALON EXTINGUISHES FLAMES BY CHEMICALLY INTERRUPTING COMBUST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NECESSARY IF PROPER ENGINEERING  
CONTROLS ARE IN PLACE. IF PEL/TLV ARE EXCEEDED,USE POSITIVE  
PRESSURE AIR-SUPPLIED RESPIRATOR. REVIEW 29CFR1910.134  
INSTRUCTIONS/WARNINGS AS WELL AS NIOSH-RESPIRATOR DECISION LOGIC  
PUB87.108.

Ventilation:PROVIDE  
SUFFICIENT GENERAL/LOCAL EXHAUST VENTILATION IN  
PATTERN/VOLUME TO CONTROL INHALATION EXPOSURES BELOW PEL/TLV.

Protective Gloves:LINED BUTYL OR AS REQUIRED FOR TASK.

Eye Protection:CHEMICAL SPLASH TYPE OR AS REQ. FOR TASK

Other Protective Equipment:AS REQUIRED TO MINIMIZE EXPOSURE & MAXIMIZE  
INDIVIDUAL PROTECTION.

Work Hygienic Practices:OBSERVE PROCEDURES SET FORTH BY SAFETY/HH  
PERSONNEL FOR USE OF THIS MATERIAL FOR TASK AT HAND.

Supplemental Safety and Health

SMALL CONC(5%) OF HALON

EXTINGUISH FLAMES BY CHEMICALLY INTERRUPTING  
COMBUSTION-NOT BY REPLACING O<sub>2</sub>. HOWEVER,VAPORIZATION OF EXCESSIVE  
AMTS CAN DEplete OR REPLACE O<sub>2</sub> NEEDED FOR BREATHING; GENERIC M  
SDS' ON NSN IDENTIFIED BY "DCSC". UPON RECEIPT OF A MFR'S MSDS  
UNDER THIS NSN, THE GENERIC WILL BE REMV.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-72F/-58C

Melt/Freeze Pt:M.P/F.P Text:-270F/-168C

Decomp Temp:Decomp Text:900F/482C

Vapor Pres:10738 @

70F

Vapor Density:5.14

Spec Gravity:1.538

Evaporation Rate & Reference:RAPID; REFERENCE UNK

Solubility in Water:0.03 % 77F

Appearance and Odor:COLORLESS LIQUID W/SLIGHT ETHEREAL ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ACTIVE METALS (EG ALKALINE EARTH & ALKALINE EARTH METALS, POWERED AL,  
ZN, BE, ETC.) & METAL HYDRIDES.

Stability Condition to Avoid:FLAMES OR HOT SURFACES >900F CAN  
CAUSE

DECOMPOSITION OF MATERIAL.

Hazardous Decomposition Products:AT HI-TEMPS(>900F); HF,HBR,FREE BR,  
POSSIBLE CARBONYL HALIDES, & OXIDES OF BROMINE, FLUORINE, OR  
CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:COMPLY W/ALL FEDERAL,STATE, & LOCAL REGULATIONS.  
RECLAIM MATERIAL IN A SUITABLE VAPOR RECOVERY SYSTEM/EQUIPMENT.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated f

or use by elements of the Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.