View NSN Online: https://aerobasegroup.es/nsn/6810-00-286-0458

CSD INC. -- TOLUENE-METHYL ISOBUTYL KETONE MIXTURE -- 6810-00-286-0458

Product ID:TOLUENE-METHYL ISOBUTYL KETONE MIXTURE MSDS Date:07/11/1986 FSC:6810 NIIN:00-286-0458 MSDS Number: BGXQT === Responsible Party === Company Name:CSD INC. Address:5 HACKBERRY LANE Box:687 City:CONROE State:TX ZIP:77305 Country:US Info Phone Num:409-756-1065 Emergency Phone Num:409-756 -1065 CAGE: JO933 === Contractor Identification === Company Name: CHEMICAL SPECIALISTS AND DEVELOPMENT INC Address:2210 HACKBERRY LN Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE:4N760 Company Name:CSD INC. Address:5 HACKBERRY LANE Box:687 City:CONROE State:TX ZIP:77305 Country:US Phone:409-756-1065 CAGE: JO933 Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 50% **OSHA PEL**

:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III) CAS:108-10-1 RTECS #:SA9275000 Fraction by Wt: 50% OSHA PEL:100 PPM/75 STEL ACGIH TLV:50 PPM/75 STEL; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 3540 MG/KG (MIX AVG.) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: VAPOR IRRITATES EYES, NOSE AND THROAT; IS ANESTHETIC. LIQUID IS IRRITATING TO SKIN, CAUSING DERMATITIS. CHRONIC: BRAIN CELL DAMAGE MAY RESULT FROM LONG TERM INHALATION OF TOLUENE VAPOR. RESPIRA TORY TRACT IRRITATION.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE, SKIN & RESPIRATORY TRACT IRRITATION. MAY CAUSE HEADACHE,

NARCOSIS, COMA, DERMATITIS, MUSCLE FATIGUE,

WEAKNESS, DIZZINESS, NERVOUSNESS, PARESTHESIA, PHOTOPHOBIA, AND CONFUSION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. GET MEDICAL ATTENTION. EYES:

IMMEDIATELY FLUSH WITH PLENTY OF WATER

FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. IF IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION

Flash Point Method:TCC Flash Point:52F Lower Limits:1.4 Upper Limits:7.5 Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:WATER MAY BE UNSUITABLE AS AN

EXTINGUISHING MEDIA, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. AVOID SPREADING BURNING LIQUID WITH WATER.

S

pill Release Procedures:SMALL SPILL: WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBANT. PUT IN DISPOSAL CONTAINER. LARGE SPILL: EVACUATE AND VENTILATE AREA. ELIMINATE SOURCES OR IGNITION. STOP LEAK IF POSSIBLE. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUID. FLUSH RESIDUE.

Neutralizing Agent:NOT APPLICABLE.

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA AWAY FROM IGNITION SOURCES . KEEP CONTAINERS CLOSED WHEN NOT IN

USE. PROTECT CONTAINER FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATE D CLOTHING BEFORE REUSE.

- Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW P
- EL(TLV), USE NIOSH/MSHA APPROVED AIR-SUPPLIED MASK AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL): EXPLOSION-PROOF VENTILATION EQUIPMENT. LOCAL EXHAUST: FACE VELOCITY 60 FPM IN CONFINED AREA. Protective Gloves:NEOPRENE, NITRILE, OR VPC

Eye Protection: CHEMICAL SPLASH GOGGLES WITH FACE SHIELD

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED. Wor k Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS. DO NOT SMOKE IN WORK AREA.

HCC:F2 Boiling Pt:B.P. Text:231F,111C Vapor Pres:40 Vapor Density:3.45 Spec Gravity:0.836 Evaporation Rate & amp; Reference :1.65(N-BUTYL ACETATE = 1) Solubility in Water:MODERATE Appearance and Odor:CLEAR, COLORLESS LIQUID, AROMATIC HYDROCARBON ODOR Percent Volatiles by Volume:100

 Stability Indicator/Materials to Avoid:YES
CAUSTIC, AMINES, ALKANOLAMINES, AMMONIA, HALOGENS, ORGANIC & INORGANIC ACIDS, STRONG OXIDIZERS & CHLORINATED COMPOUNDS.
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OPEN FLAMES
Hazardous Decomposition Products:CAR
BON MONOXIDE, CARBON DIOXIDE

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be acc urate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.