View NSN Online: https://aerobasegroup.es/nsn/8010-00-242-6318

PRATT & LAMBERT INC. -- LACQUER C/N GLOSS 21 BLUE 15044 ID786504 -- 8010-00-242-6318
========== Product Identification ==========

Product ID:LACQUER C/N GLOSS 21 BLUE 15044 ID786504
MSDS Date:12/15/1988
FSC:8010
NIIN:00-242-6318
MSDS Number: BHBWP
=== Responsible Party ===
Company Name:PRATT & LAMBERT INC.
Address:16116 E 13TH ST
Box:2153
City:WICHITA
State:KS
ZIP:67201
Country:US
Preparer's Name:W.A. ELLIS
ON
CAGE:PRATT
=== Contractor Identification ===
Company Name:PRATT & LAMBERT
Address:250 PETTIT AVE
Box:2153
City:BELLMORE
State:NY
ZIP:11710
Country:US
Phone:800-647-2253
CAGE:PRATT
Company Name:PRATT AND LAMBERT INC
Address:Box:6027
City:CLEVELAND
State:OH
ZIP:44101-1027
Country:US
Phone:216-566-2902
CAGE:61196

========== Composition/Information on Ingredients ==========

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
E

PA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)
CAS:8002-05-9
RTECS #:S
E7449000
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 8990

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
OSHA PEL:100 PPM

Ingred Name:VOL ORGANIC CMPD 5.3 LB/GL LESS WATER & NPRS* 600 G/L LESS WATER VOC 24.8 LB/GAL SOLIDS 2976 G/L SOLIDS CALCULATED
RTECS #:9999999VO

=

========== Hazards Identification ==========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:SWALLOWING/GASTROINTESTINAL IRRITATION,NAUSEA,VOMITING. INHALATION/MAY CAUSE NOSE,THROAT IRRIT. HIGH CONCENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION. EYE/IRRITATION. SKIN/MAY CAUSE DE FATTING, IRRITATION OF THE SKIN.
Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS A POTENTIAL CARC
INOGEN BY THE NATURAL TOXICOLOGY PROGRAM.
Effects of Overexposure:PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. DELIBERATE CONCENTRATION AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

========== First Aid Measures ==========

First Aid:SWALLOWING/DO NOT INDUCE VOMITING. GET MED ATTN. INHALATION/GET FRESH AIR IMMED.IF BREATHING HAS STOPPED,GIVE ARTIFICIAL RESPIRATION.GET MED ATTN. E
YE/FLUSH WITH LG AMT OF WATER FOR 15 MIN. GET MED AT TN. SKIN/FLUSH THE CONTAMINATED AREA W/LG AMT OF WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A DR. NOTE TO DR. ANY TREATMENT FOR OVEREXP S/B DIRECTED AT THE CONTROL OF SYMPTOMS & CLINICAL CONDITIONS.

========== Fire Fighting Measures ==========

Flash Point:20F/-6.67C
Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SE
LF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL EXPOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PROD MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMED APPARENT. OBTAIN MEDICAL ATTN. WARNING:FLAMMABLE.

========== Accidental Release Measures ==========

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE & CONTAIN SPILL WITH INERT MATERIAL. U

SE COVERED METAL CONT FOR RECOVERY OR
DISPOSAL. USE ONLY NON-SPARKING TOOLS. DONT CONTAMINATE
SEWERS,STREAMS AND GROUNDWATER. KEEP SPECTATORS AWAY. WEAR
APPROPRIATE RESPIRATORS.

========== Handling and Storage ==========

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT REUSE CONTAINERS. CONTAINERS SHOULD BE
GROUNDED AND BONDED TO THE RECEIVING CONTAINER.
DO NOT
WELD/BRAZE/CUT ON EMPTY CONT. NEVER USE PRESSURE TO EMPTY.DRUM NOT
A PRESSURE VESSEL. CLOSE AFTER E ACH USE. DO NOT TAKE INTERNALLY.

========== Exposure Controls/Personal Protection ==========

Respiratory Protection:IN RESTRICTED AREAS A NIOSH RESPIRATOR MAY BE
REQUIRED. CONFINED AREAS A NIOSH/MSHA APPROVED AIR SUPPLIED
RESPIRATOR. SEE OSHA 29CFR1910.134. RESPIRATORY PROTECTION AND
RESPIRATORY PROTECTION MANUAL A ND GUIDELINE, AMER IND HYGIENE
ASSOC.
Vent
ilation:GENERAL AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME
AND PATTERN TO MAINTAIN CONCENTRATIONS OF SUBSTANCES.
Protective Gloves:IMPERMEABLE GLOVES.
Eye Protection:SAFETY SPECTACLES.
Other Protective Equipment:NOT LIKELY TO BE NEEDED.
Supplemental Safety and Health
NONE LISTED.

========== Physical/Chemical Properties ==========

Boiling Pt:B.P. Text:180F/302F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:78

===
========== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF
IGNITION.
Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRODUCE
SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE. OXIDES OF NITROGEN MAY
BE GENERATED.
Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT,SPARKS AND
FLAME.

==========

= Disposal Considerations ==========

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. DISPOSE IAW FEDERAL,STATE AND LOCAL LAWS/REGULATIONS. RCRA CLASS IFICATION D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.