

PRATT & LAMBERT INC. -- LACQUER C/N GLOSS YELLOW 13538 11 ID786310 -- 8010-00-248-2838
===== Product Identification =====

Product ID:LACQUER C/N GLOSS YELLOW 13538 11 ID786310

MSDS Date:12/15/1988

FSC:8010

NIIN:00-248-2838

MSDS Number: BHBWR

=== Responsible Party ===

Company Name:PRATT & LAMBERT INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. E

LLISON

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
OSHA PEL:100 PPM

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ALIPHATIC HYDROCARBON (VP MM HG @ 20 DEG C 12)
CAS:64742-89-8
OSHA PEL:NONE ESTABLISHED

D

ACGIH TLV:NONE ESTABLISHED

Ingred Name:VOL ORGANIC CMPD 5.1 LB/GL LESS WATER & NPRS* 612 G/L LESS
WATER VOC 20.4 LB/GAL SOLIDS 2448 G/L SOLIDS CALCULATED
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES
Health Hazards Acute and Chronic:SWALLOWING/GASTROINTESTINAL
IRRITATION,NAUSEA,VOMITING. INHALATION/MAY CAUSE NOSE,THROAT IRRIT.
HIGH CONC
ENTRATIONS MAY CAUSE ACUTE CENTRAL NERVOUS SYSTEM
DEPRESSION. EYE/IRRITATION. SKIN/MAY CAUSE DE FATTING, IRRITATION
OF THE SKIN.
Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS LISTED AS
A POTENTIAL CARCINOGEN BY THE NTP. CHROMIUM & CHROMIUM POTENTIAL
CARCINOGENS.
Effects of Overexposure:REPEATED OVEREXPOSURE TO CHROMATES MAY CAUSE
LUNG DAMAGE. CHRONIC OVEREXP TO LEAD MAY RESULT IN DAMAGE TO BLOOD
FORMING, NERVOUS,URINARY AND REPRODUCTIVE SYSTEMS.
SYMPTOM
S:METALLIC TASTE,LOSS OF APPET
ITE,ANXIETY,CONSTIPATION,NAUSEA,WEAKNESS,INSOMNIA,HEADACHE,MUSCLE &
JOINT PAIN,FINE TREMORS,NUMBNESS,DIZZINESS.

===== First Aid Measures =====

First Aid:SWALLOWING:DO NOT INDUCE VOMITING.GET MED ATTN.
INHALATION:GET FRESH AIR IMMED. IF BREATHING HAS STOPPED,GIVE
ARTIFICIAL RESPIRATION. GET MED ATTN. EYE:FLUSH WITH LG AMT OF
WATER FOR 15 MIN. GET MED A TTN. SKIN:FLUSH THE CONTAMINATED AREA
W/LG AMT OF W
ATER. REMOVE CONTAMINATED CLOTHING.CONSULT A DR. NOTE
TO DR. ANY TREATMENT FOR OVEREXP S/B DIRECTED AT THE CONTROL OF
SYMPTOMS & CLINICAL CONDITIONS.

===== Fire Fighting Measures =====

Flash Point:20F/-6.67C
Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PREFERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
MAY BE INEFFECTIVE,BUT CAN BE USED TO COOL EXPOSED CONTAINERS.IF

WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PROD MAY
CAUSE HEALTH HAZARD.SYMPTOMS MAY NOT BE IMMED APPARENT. OBTAIN
MEDICAL ATTN.WARNING:FLAMMABLE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL IGNITION SOURCES.DIKE & CONTAIN SPILL
WITH INERT MATERIAL. USE COVERED METAL CONT FOR RECOVERY OR
DISPOSAL. USE ONLY NON-SPARKING TOOLS. DONT CONTAMINATE
SEWERS,STREAMS
AND GROUNDWATER. KEEP SPECTATORS AWAY. WEAR
APPROPRIATE RESPIRATORS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.
Other Precautions:DO NOT REUSE CONTAINERS. CONTAINERS SHOULD BE
GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT
WELD/BRAZE/CUT ON EMPTY CONT. NEVER USE PRESSURE TO EMPTY. DRUM NOT
A PRESSURE VESSEL. CLOSE AFTER E
ACH USE.DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED AREAS A NIOSH RESPIRATOR MAY BE
REQUIRED. CONFINED AREAS A NIOSH/MSHA APPROVED AIR SUPPLIED
RESPIRATOR. SEE OSHA 29CFR1910.134. RESPIRATORY PROTECTION AND
RESPIRATORY PROTECTION MANUAL A ND GUIDELINE, AMER IND HYGIENE
ASSOC.
Ventilation:GENERAL AND LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME
AND PATTERN TO MAINTAIN CONCENTRATIONS OF SUB
STANCES.
Protective Gloves:IMPERMEABLE GLOVES.
Eye Protection:SAFETY SPECTACLES.
Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT.SEE OSHA
STANDARD FOR LEAD.
Supplemental Safety and Health
NONE LISTED.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:181F/302F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stabili

ty Indicator/Materials to Avoid: YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products: BURNING/WELDING/CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE. OXIDES OF NITROGEN MAY BE GENERATED.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:

INCINERATE ONLY IN EPA PERMITTED FACILITY. DO

NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. DISPOSE IAW FEDERAL, STATE AND LOCAL LAWS/REGULATIONS. RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.