

PRATT & LAMBERT, INC. -- LAC SPRAYING II WHITE 17875 ID 793716 -- 8010-00-165-6140

=====
Product Identification
=====

Product ID:LAC SPRAYING II WHITE 17875 ID 793716

MSDS Date:12/15/1988

FSC:8010

NIIN:00-165-6140

MSDS Number: BHCFM

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISON

C

AGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOH

OL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE
CAS:9004-70-0
RTECS #:QW0970000
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:
TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
OSHA PEL:100 PPM

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)
CAS:117-81-7
RTECS #:TI0350000
OSHA PEL:5 MG/M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:ALIPHATIC HYDROCARBON (VP MM HG @ 20 DEG C 12)

CAS:64742-89-8
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOL ORGANIC CMPD 5.5 LB/GL LESS WATER & NPRS* 660 G/L LESS
WATER VOC 29.2 LB/GAL SOLIDS 3504 G/L SOLIDS CALCULATED
RTECS #:9999999VO

=====
===== Hazards Identification =====
=====

Routes of Entry: I

Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING-GASTROINTESTINAL

IRRITATION, NAUSEA, VOMITTING. INHALATION-NOSE/THROAT

IRRITATION/HEADACHES,DIZZINESS/NAUSEA AND CONFUSION.

EYE-IRRITATION. SKIN PRIMARY IRRITANT, MAY CAUSE DEFATTING/IRRITA
TION OF THE SKIN.

Explanation of Carcinogenicity:DI(2-ETHYLHEXYL) PHTHALATE IS A
POTENTIAL CARCINOGEN AS LISTED BY THE NATIONAL TOXICOLOGY PROGRAM.

Effects

Effects of Overexposure:OVEREXPOSURE TO TOLUENE MAY CAUSE LIVER DAMAGE.

OVEREXPOSURE TO SOLVENTS-PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:SWALLOWING-DO NOT INDUCE

VOMITING/GET MED ATTN. INHALATION-REMOVE TO FRESH AIR/GIVE

ARTIFICIAL RESPIRATION IF REQ/GET MED ATTN. EYE-FLUSH WITH

WATER/GET MED ATTN. SKIN-WASH WITH WATER.CONSULT A DOCTOR

=====
===== First Aid Measures =====
=====

First Aid:NOTES TO PHYSICIAN-ANY TREATMENT THAT MIGHT BE REQUIRED FOR
OVEREXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE
CLINICAL CONDITIONS.

=====
===== Fire Fighting Measures =====
=====

Flash Point:20F/-6.67C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:FOG NOZZLES ARE PREFERABLE IF WATER IS USED.

WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO C

OOL
CONTAINERS.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION MAY CAUSE HEALTH HAZARD. GET MEDICAL ATTN.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROPRIATE RESPIRATORS/ELIMINATE ALL IGNITION SOURCES/DIKE SPILL WITH INERT MATERIAL/RECOVER & DISPOSE OF IN METAL CONTAINERS. DO NOT CONTAMINATE SEWERS/STREAMS/GROUNDWATER.

===== Handling and Storage =====

Handling and Storage

Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QTY IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT WELD/BRAZE/CUT ON EMPTY CONTAINER-NEVER USE PRESSURE TO EMPTY-DRUM IS NOT A PRESSURE VESSEL. CONTAINERS-GROUNDED/BONDED TO THE RECEIVING CONTAINER.DO NOT RE-USE CONTAINERS. CLOSE AFTER EACH USE . DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN RESTRICTED VENTILATION A NIOSH APPROVED RESPIRATOR.

IN CONFINED AREAS USE A NIOSH/MSHA APPROVED RESPIRATOR. REFER TO OSHA 29CFR1910.134 AND RESPIRATORY PROTECTION A MANUAL AND GUIDELINE AMERICAN INDUSTRIAL HYGIENE ASSOC.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION TO MAINTAIN HAZARDOUS SUBSTANCES LISTED IN SEC II BELOW THE LOWEST LIMITS.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWERS.

Supplemental Safety and Health

ONE

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175F/302F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:81

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING/WELDING/CUTTING WILL PRO

DUCE
SMOKE, CARBON MONOXIDE & CARBON DIOXIDE PLUS OXIDES ON NITROGEN MAY
BE GENERATED.

Conditions to Avoid Polymerization:WILL NOT OCCUR.KEEP AWAY FROM
HEAT,SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW FEDERAL/STATE/LOCAL LAWS.INCINERATE
ONLY IN EPA PERMITTED FACILITY. CONTAMINATED ABSORBANT DISPOSE OF
IN A HAZARDOUS WASTE LANDFILL IAW FEDERAL/STATE/LOCAL REGULATIONS.
RCRA CLASSIFICATION D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.