View NSN Online: https://aerobasegroup.es/nsn/6810-00-782-2686

CSD, INC. -- TECSOL 1 SOLVENT ANHYDROUS -- 6810-00-782-2686

============ Product Identification ==============

Product ID:TECSOL 1 SOLVENT ANHYDROUS

MSDS Date:07/01/1988

FSC:6810

NIIN:00-782-2686

MSDS Number: BHCGF === Responsible Party === Company Name:CSD, INC. Address:5 HACKBERRY

Box:687

City:CONROE

State:TX ZIP:77305 Country:US CAGE:KO005

=== Contractor Identification ===

Company Name: CHEMICAL SPECIALISTS AND

DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone: 409-756-1065

CAGE:4N760

Company Name: CSD, INC. Address: 5 HACKBURY ST

Box:687

City:CONROE

State:TX ZIP:77305 Country:US

Phone:409-756-1065

CAGE:KO005

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 89% OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name: ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000 Fraction by Wt: 5% OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000 Fraction by Wt: 4%

OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000 Fraction by Wt: 1%

OSHA PEL:500 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9293

Ingred Name: METHYL ISOBUTYL KETONE (SARA III)

CAS :108-10-1

RTECS #:SA9275000 Fraction by Wt: 1%

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========== Hazards Identification ===========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Effects of Overexposure:EYE: LIQUID AND VAPOR CAN CAUSE IRRITATION. SKIN: LOW HAZARD FOR USUAL INDUSTRIAL HANDLING INHALATION: MAY

CAUSE UPPER RESPIRATORY TRACT IRRITATION AND NARCOSIS.

======= First Ai

d Measures ===========
First Aid:EYE: FLUSH W/LARGE QUANTITIES OF WATER FOR 15 MINS. GET MEDICAL ATTENTION. SKIN: WASH THOROUGHLY WITH WATER. INHALATION: REMOVE TO FREESH AIR. IF BREATHING IS DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENT ION.
======================================
Flash Point Method:SCC Flash Point:>102F/39C Autoignition Temp:Autoignition Temp Text:>404C Extinguishing Media:NFPA CLASS B FIRE EXTINGUISHERS(CARBON DIOXIDE,ALL
PURPOSE DRY CHEM OR ALCOHOL FOAM). USE POLYMER FOAM FOR LG FIRES. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE, BUT MAY BE USEDTO COOL EXPOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKSAND FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.
======== Accidental Release Measures ======
Spill Release Procedures:REMOVE ALL SOURCES INGNITION. USE WATER SPRAY TO DISPERSE VAPORS AND TO DILUTE TO A NONFLAMMABLE MIXTURE. PREVENT RUNOFF FROM ENTERING DRAINS, SEW-ERS/STREAMS. COLLECT W/ABSORBANT FOR SMALL SPILLS.
======================================
Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,& OPEN FLAME. KEEP CON-TAINERS CLSD. VAPORS ARE > AIR & WILL TRAVEL ALONGGROUND. Other Precautions:EMPTY CONTAINE R HAS A RESIDUE SO DO NOT CUT, DRILL, OR WELD ON OR NEAR THEM.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPOR IN AREAS ABOVE THE TLV LIMITS. Ventilation:MECHANICAL VENTILATION OR LOCAL EXHAUST Protective Gloves:NEOPREME Eye Protection:GOGGLES Other Protective Equipment:EYE WASH Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
HCC:F5

HCC:F5 Boiling Pt:

B.P. Text:280F-388F
Vapor Density:>AIR
Evaporation Rate & Evaporation R
Percent Volatiles by Volume:62

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS
Stability Condition to Avoid:EXCESSIVE HEAT AND SOURCES OF IGNITION
Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization: HEAT SPARKS AND FLAME

=======================================	
posal Considerations	

Waste Disposal Methods:MIX W/COMPATIBLE LESS FLAMMABLE CHEMICAL & INCINE- RATE; OBSERVE ALL FEDERAL, STATE, AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.