

EVERSEAL MANUFACTURING CO., INC. -- GRAY GLOSS ALKYD ENAMEL C-16187 --  
8010-00-286-7731

===== Product Identification =====

Product ID:GRAY GLOSS ALKYD ENAMEL C-16187  
MSDS Date:10/21/1987  
FSC:8010  
NIIN:00-286-7731  
MSDS Number: BHDHP  
=== Responsible Party ===  
Company Name:EVERSEAL MANUFACTURING CO., INC.  
Address:475 BROAD AVENUE  
City:RIDGEFIELD  
State:NJ  
ZIP:07657  
Country:US  
Emergency Phone Num:201-943-4986  
CAGE:EO432  
=== Contractor Identification ===  
Company Name  
e:EVERSEAL MANUFACTURING CO., INC.  
CAGE:EO432  
Company Name:EVERSEAL MFG CO INC  
Address:475 BROAD AVE  
Box:City:RIDGEFIELD  
State:NJ  
ZIP:07657-2329  
Country:US  
Phone:201-943-4986  
CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN  
Fraction by Wt: 34%  
ACGIH TLV:NA

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 17%  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE  
CAS:1309-37-1  
Fraction by Wt:

2%  
OSHA PEL:10 MG/M3 (FE)  
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:MINERAL SPIRITS  
VAPOR PRESSURE 2  
CAS:64742-88-3  
Fraction by Wt: 45%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Effects of Overexposure:EYE/SKIN: IRRITATION  
INHALATION: DIZZINESS, NAUSEA,  
POSSIBLE UNCONSCIOUSNESS

===== First Aid Measures =====

First Aid:INHALATION: REM  
OVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION  
IF NECESSARY. SKIN: WASH WITH SOAP AND WATER.  
EYE: FLUSH WITH WATER CONSULT  
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:105F/40.56C  
Lower Limits:1.0  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING  
MEDIUM. FIREFIGHTERS SHOULD WEAR SELF CONTAINED BREATHING  
APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE ADEQUATE  
VENTILATIONABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE  
SPARK PROOF SCOOP FOR LARGER SPILLS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION  
SOURCES.  
Other Precautions:NPCA/HMIS RATING 3,2,0,H

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV

MAY BE EXCEEDED, USE CARTRIDGE FUME MASK.  
Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES  
Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323-390F  
Vapor Density:> AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:NA  
Hazardous Decomposition Products:CARBON MONOXIDE/DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,  
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense.  
The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.