

EVERSEAL MANUFACTURING CO., INC. -- GRAY GLOSS ALKYD ENAMEL C-16187 --
8010-00-286-7731

===== Product Identification =====

Product ID:GRAY GLOSS ALKYD ENAMEL C-16187
MSDS Date:10/21/1987
FSC:8010
NIIN:00-286-7731
MSDS Number: BHDHP
=== Responsible Party ===
Company Name:EVERSEAL MANUFACTURING CO., INC.
Address:475 BROAD AVENUE
City:RIDGFIELD
State:NJ
ZIP:07657
Country:US
Emergency Phone Num:201-9
43-4986
CAGE:EO432

=== Contractor Identification ===
Company Name:EVERSEAL MANUFACTURING CO., INC.
CAGE:EO432
Company Name:EVERSEAL MFG CO INC
Address:475 BROAD AVE
Box:City:RIDGFIELD
State:NJ
ZIP:07657-2329
Country:US
Phone:201-943-4986
CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN
Fraction by Wt: 34%
ACGIH TLV:NA

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 17%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TD

UST; 9293

Ingred Name:IRON OXIDE

CAS:1309-37-1

Fraction by Wt: 2%

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:MINERAL SPIRITS

VAPOR PRESSURE 2

CAS:64742-88-3

Fraction by Wt: 45%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Effects of Overexposure:EYE/SKIN: IRRITATION

INHALATION: DIZZINESS, NAUSEA,
POSSIBLE UNCONSCIOUSNESS

=====
===== First
Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION
IF NECESSARY. SKIN: WASH WITH SOAP AND WATER.
EYE: FLUSH WITH WATER CONSULT
PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:105F/40.56C

Lower Limits:1.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard:WATER NOT A SUITABLE EXTINGUISHING
MEDIUM. FIREFIGHTERS SHOULD WEAR SELF CONTAINED BR
EATHING
APPARATUS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE ADEQUATE
VENTILATNABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE
SPARK PROOF SCOOP FOR LARGER SPILLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN IGNITION
SOURCES.

Other Precautions:NPCA/HMIS RATING 3,2,0,H

=====
===== Exposure Controls/P

Personal Protection =====

Respiratory Protection:IF TLV MAY BE EXCEEDED, USE CARTRIDGE FUME MASK.
Ventilation:SUFFICIENT TO ENSURE LEL NOT ACHIEVED
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323-390F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volat
iles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:NA
Hazardous Decomposition Products:CARBON MONOXIDE/DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information
is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.