

CON-LUX COATINGS, INC. -- ENAMEL ALKYD LSTRLES QUICK DRY YELLOW 33538 --
8010-00-297-0811

===== Product Identification =====

Product ID:ENAMEL ALKYD LSTRLES QUICK DRY YELLOW 33538
MSDS Date:07/07/1989
FSC:8010
NIIN:00-297-0811
MSDS Number: BHDKM
=== Responsible Party ===
Company Name:CON-LUX COATINGS, INC.
Address:226 TALMAGDE ROAD
Box:847
City:EDISON
State:NJ
ZIP:08818-0847
Country:US
Info Phone Num:(206) 287-4000
Emergency Phone Num:(206) 287-4000
CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC
Address:226 TALMADGE RD
Box:847
City:EDISON
State:NJ
ZIP:08818-0847
Country:US
Phone:732-287-4000
CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPHTHA (LIGROINE)
CAS:8032-32-4
RTECS #:OI6180000
Fraction by Wt: >1%
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 11%
OSHA PEL:100 PPM
ACGIH

TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: >1%
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:LEAD CHROMATE
CAS:1344-37-2
Fraction by Wt: 19%
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;
8990

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 2%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Effects of Overexposure:IRRITATION OF EYES & SKIN MAY OCCUR
W/OVEREXPOSURE.CONTINUED BREATHING OF VAPORS MAY IRRITATE
RESPIRATORY TRACT CAUSING HEADACHE, NAUSEA & DIZZINESS.REPORTS
HAVE ASSOC REPEATED & PROLONGED OVEREXP

OSURE TO SOLVENTS
W/PERMANENT BRAIN & NERVOUSSYSTEM DAMAGE.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.RESTORE RESPIRATION IF
NECESSARY.EYE:FLUSH IMMEDIATELY W/COPIOUS QTYS OF WTR FOR 15 MINS
MINIMUM.CONSULT A PHYSICIAN.SKIN:WASH AFFECTED AREA W/SOAP &
WTR.REMOVE CONTAMINATED CLOTHING.INGESTION:DRINK 1/2 GLASSES OF
WTR TO DILUTE.DO NOT INDUCE VOMITING.IF SPONTANEOUS VOMITING OCCURS
KEEP HEAD AT OR BELOW
W KNEES TO PREVENT ASPIRATION INTO
LUNGS.CONSULT PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:45F 7.22C
Extinguishing Media:FOAM,CARBON DIOXIDE CO2,DRY CHEMICAL,WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES W/ONE OF THE ABOVE
EXTINGUISHING MEDIA.WATER MAY BE USED TO COOL DOWN UNOPENED
CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT.DO NOT USE IN
AREAS WHERE SPARKS OR
OPEN FLAMES ARE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.WEAR
APPROPRIATE PERSONAL PROTECTION EQUIP & APPROVED RESPIRATOR.CONTAIN
SPILL W/ABSORBENT MATERIAL & PUT INTO VAPOR TIGHT
CONTAINERS.PREVENT MATERIAL FROM CONTACTING ANY WTR SOURCES OR
SEWERS LEADING TO SURFACE WTRS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN
AREAS DESIGNED TO COMPLY
W/ANSI/NFPA 30 FLAMMABLE & COMBUSTIBLE LIQUIDS CODE.
Other Precautions:GROUND CONTAINERS WHEN POURING LIQS/PDRS TO AVOID
STATIC CHARGE BUILD UP.DO NOT HANDLE UNTIL MANUFACTURERS SAFETY
PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.PROVIDE ADEQUATE VENT &
RESPIRATORY PROTECTION DURING WELDING OR FLAME CUTTING COATING

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN AREAS,USE APPROVED RESPIRATOR

TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION.IN RESTRICTED VENT AREA USE APPROVED RESPIRATOR DESIGN TO REMOVE A COMBO OF P ARTICLES & VAPORS.

Ventilation:YES

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY EYE WEAR PROTECT AGAINST SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM FACILITIES.

Supplemental Safety and Health

NK

=====

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:148 - 315F

Vapor Density:>AIR

Evaporation Rate & Reference: