

CON-LUX COATINGS, INC. -- ENAMEL GLOSS 13538, YELLOW -- 8010-00-527-2045

=====
Product Identification
=====

Product ID:ENAMEL GLOSS 13538, YELLOW

MSDS Date:09/26/1984

FSC:8010

NIIN:00-527-2045

MSDS Number: BHDMM

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMAGDE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:(206) 287-4000

Emergency Phone

Num:(206) 287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 38.2%

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE

CAS:1344-37-2

Fraction by Wt: 27%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Effects of Overexposure:EYE/SKIN: IRRITATION MAY OCCUR WITH
OVEREXPOSURE. INHALATION: CONTINUED
BREATHING OF VAPORS, IN SOME INSTANCES, MAY IRRITATE
RESPIRATORY TRACT AND CAUSE HEADACHE OR DIZZINESS, WHICH IS NORMAL
FOR SOLVENTBASE PRODUCTS.

=====
First Aid Measures
=====

First Aid:SKIN/EYE
: FLUSH WITH PLENTY OF WATER.
INHALATION: REMOVE TO FRESH AIR. IF IRRITATION
PERSISTS, CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:105F/40.56C
Upper Limits:1.0
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE
EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN UNOPENED
CONTAINERS IN VICINITY.
Unusual Fire/Explosion
Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN
AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
PROLONGED BREATHING OF VAPORS. VENTILATE AREA. CLEAN UP
WITH ABSORBENT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND
PROTECTED FOR STORAGE OF NFPA CLASS

II FLAMMABLE LIQUIDS.

Other Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLELIQUIDS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR/OPEN AREAS USE APPROVED FILTER RESPIRATOR. IN RESTRICTED VENTILATION AREAS USE APPROVED CHEMICAL FILTERS.

Ventilation:GENERAL OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV BELOW LIMIT.

Protective Gloves:REQUIRED FOR LONG EXPOSURE

Eye Protection:SAFETY GLASSES
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT W/CONTAMINATED CLOTHING.

Supplemental Safety and Health
NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:315-380F
Vapor Density:> AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:60

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:
CO, CO2

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and discl

aims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.