

NELSON TECHNICAL COATINGS INC -- PAINT READY MIXED -- 8010-00-664-9077

===== Product Identification =====

Product ID:PAINT READY MIXED

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-9077

MSDS Number: BHDSV

=== Responsible Party ===

Company Name:NELSON TECHNICAL COATINGS INC

Address:2147 N TYLER AVE

City:SOUTH EL MONTE

State:CA

ZIP:91733-2754

Country:US

Info Phone Num:213-575-3333

Emergency Phone Num:21

3-575-3333

CAGE:60800

=== Contractor Identification ===

Company Name:NELSON TECHNICAL COATINGS INC

Address:2147 N TYLER AVE

Box:City:SOUTH EL MONTE

State:CA

ZIP:91733-2754

Country:US

CAGE:60800

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 14%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-3

0-6
RTECS #:SE7555000
Fraction by Wt: 49%
OSHA PEL:100 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

===== First Aid Measures =====
=====

First Aid:FUMES: REMOVE TO FRESH AIR. RESTORE BREATHING KEEP WARM &
QUIET. CALL PHYSICIAN.SPLASH EYE: FLUSH WITH LARGE QUANTITIES OF
RUNNING WATER FOR 15 MIN. SEEK MEDICAL HELP. SKIN: WASH WELL WITH
RUNNING WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:86F/30.00C
Lower Limits:1.2
Upper Limits:1.0
Extinguishing Media:NFP CLASS B, EXTINGUISHERS,CO21, DRY CHEMICAL, OR
FOAM DESIGNED TO EXTINGUISH NFPA CL I LIQUID FIRES
Fire Fighting Procedures:WTR SPRAY MAY BE INEFFECT, WTR MAY BE USED TO
COOL CONTAINER TO PREVENT PRESSUREBUILD UP & POSSIBLE EXPLOSION
WHEN EXPOSED TO EXTREME HEAT. USE FOG NOZZLES
Unusual Fire/Explosion Hazard:PRESSURE MAY BUILD UP WHEN CLOSED
CONTAINER IS EXPOSED TO HEAT. DO NOT APPLY TO HOT SURFACE. PAINT
VAPORS MAY CAUSE VIOLENT EXPLOSION. USE EXPLOSION PROOF EQUIP

===== Accidental Release Measu

res =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL OR STATIC, OR FRICTIONAL SPARKS).
AVOIDBREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE OVER 120 F. STORE LARGE QUANITITES INBLDS DESIGNED & PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS
Other Precautions:DO
NOT TAKE INTERNALLY

===== Exposure Controls/Personal Protection =====

Respiratory Protection:BUREAU OF MINES APPROVED CHEMICAL-MECHANICAL FILTERS TO REMOVE PARTICALS, GAS, AND VAPOR
Ventilation:LOCAL-TO KEEP TLV/LEL OF MOST HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMIT
Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT
Eye Protection:GOGGLES OR FACE SHIELDS
Other Protective Equipment:IN CONFINED AREAS USE BUREAU OF MINES APPROVED AIRLINE TYPE RESPIRATORS OR HOODS
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:232-308 F
Vapor Density:> AIR
Spec Gravity:1.128
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
WATER
Stability Condition to Avoid:FLAME AND HIGH HEAT
Hazardous Decomposition Products:NORMALLY CARBON COMBUSTION P

RODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, &
FED-ERAL REG. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE
CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to
be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.