

HYSAN CORPORATION -- GSA DEODORANT GENERAL PURPOSE (AEROSOL) -- 6840-00-721-6055

===== Product Identification =====

Product ID:GSA DEODORANT GENERAL PURPOSE (AEROSOL)

MSDS Date:11/18/1986

FSC:6840

NIIN:00-721-6055

MSDS Number: BHDTD

=== Responsible Party ===

Company Name:HYSAN CORPORATION

Address:4309 S. MORGAN

Box:NA

City:CHICAGO

State:IL

ZIP:60609

Country:US

Info Phone Num:312-376-8981

Emergency

Phone Num:312-376-8981

Preparer's Name:M. FOGELFS

CAGE:HYSAN

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:HYSAN CORPORATION

Address:2929 ALLEN PARKWAY, SUITE 2130

City:HOUSTON

State:TX

ZIP:77019

Country:US

Phone:713-620-7740

CAGE:HYSAN

===== Composition/Information on Ingredients =====

Ingred Name:PETOLEUM

DISTILLATE (240 F - 270 F)
CAS:64742-48-9
Fraction by Wt: 1-10%
Other REC Limits:400 PPM
OSHA PEL:NK PPM

Ingred Name:PROPELLANT: C3-C4 ALKANE BLEND
CAS:68475-59-2
Fraction by Wt: 20-30%
Other REC Limits:400 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED BREATHING OF
EXCESSIVE CONCENTRATIONS MAY CAUSE
DIZZINESS, HEADACHES. EYES: MAY
CAUSE IRRITATION. INGESTION: MAY BE HARMFUL IF SWALLOWED.
ASPIRATION OF LIQUID MAY CAUSE CHEMICAL PNEUMONITIS
Effects of Overexposure:PAIN OR IRRITATION

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH PLENTY OF
WATER. CALL PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH OFF
WITH WATER. INGESTION: DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:>47 F 8.33 C
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:FOAM, DRY CHEMICAL, CO2 OR WATER SPRAY
Fire Fighting Procedures:KEEP CONTAINERS COOL. USE SHIELDING TO PROTECT
PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINER
Unusual Fire/Explosion Hazard:AT ELEVATED TEMPERATURES (OVER 130 F)
CONTAINERS MAY VENT, RUPTURE OR BURST

===== Accidental Release Measures =====

Spill Release Pro

cedures:REMOVE SOURCES OF FLAME, SPARK OR HEAT.
PROVIDE ADEQUATE VENTILATION. WIPE UP SPILLS THEN RINSE WITH
WATER

===== Handling and Storage =====

Handling and Storage Precautions:CONTENTS UNDER PRESSURE. KEEP OUT OF
REACH OF CHILDREN. DO NOT STORE WHERE TEMP. EXCEED 130 F
AVOID CONTACT WITH EYES

Other Precautions:READ ENTIRE LABEL BEFORE USING

===== Exposure Controls/Personal Protection =====

Respiratory Protection:N

ONE REQUIRED

Ventilation:LOCAL EXHAUST: NONE REQUIRED, MECHANICAL: MAINTAIN ADEQUATE
VENTILATION

Protective Gloves:NONE REQUIRED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE REQUIRED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:212

Melt/Freeze Pt:M.P/F.P Text:>32 F

Vapor Pres: