

PRATT & LAMBERT, INC. -- COAT'G POLYUR 1 COMP TAN 686 33446 ID705130 -- 8010-01-276-3638

=====  
Product Identification  
=====

Product ID:COAT'G POLYUR 1 COMP TAN 686 33446 ID705130

MSDS Date:12/13/1988

FSC:8010

NIIN:01-276-3638

MSDS Number: BHFHY

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.

A. ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty

:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE

CAS:14464-46-1

RTECS #:VV7325000

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TIT

ANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN  
1% CRYSTALLINE SILICA

CAS:61790-53-2

RTECS #:HL8600000

OSHA PEL:20 MPPCF

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

OSHA PEL:SEE T

ABLE Z3  
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)  
CAS:108-10-1  
RTECS #:SA9275000  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:POLYMERIC HEXAMETH-YLENE DIISOCYANATE  
CAS:28182-81-2  
RTECS #:NQ9170000

Ingred Name:AROMATIC HYDROCARBON  
CAS:64741-67-9

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)  
CAS:822-06-0  
RTECS #:MO1740000  
ACGIH TLV:0.005 PPM; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty  
:1 LB

Ingred Name:VOC. ORGANIC CMPD 3.5 LB/GL LESS WATER & NPRS\* 420 G/L LESS  
WATER VOC 6.7 LB/GAL SOLIDS 804 G/L SOLIDS CALCULATED.  
RTECS #:9999999VO

===== Hazards Identification =====

LD50 LC50 Mixture:YES  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:SWALLOWING: CAN CAUSE GASTROINTESTINAL  
IRR/NAUSEA/VOMIT. ASPIRATION OF MAT'L MAYCAUSE CHEM PNEUMONITIS

INHALATION: NOSE/THROAT/LUNG IRR/DAMAGE. HIGH CONCEN MAYCAUSE  
CENTRAL NERVOUS SYS DEPRESSION CHA R BY  
HEADACHES/DIZZINESS/NAUSEA/CONFU-SION. EYE: MAY CAUSE EYE IRR.  
SKIN: MAY CAUSE DEFATTING/IRRITA/SENSITIZATION.

Explanation of Carcinogenicity:IARC-CRYSTALLINE SILICA LMTED EVI  
CARCINOGENICITY IN HUMANS.TITANIUM DIOXIDE NOT POTENT  
CARCINOGEN-NTP,IARC,OSHA,ACGIH.

Effects of Overexposure:REPEATED EXPOSURE TO CRYSTALLINE SILICA MAY  
CAUSE PNEUMOCONIOSIS. REPEATED EXPO-SU

RE TO DIISOCYANATES MAY

RESULT IN RESPIRATORY SENSITIZATION IN SOME INDIVID. OVEREXPOSURE TO SOLVENTS ASSO W/PERM BRA IN/NERVOUS SYSTEM DAMAGE.

INTENTIONALMISUSE BY CONCENTRATING AND INHALING CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY CONDITIONS MAY BE AGGRA- VATED BY EXPOSURE TO CRYSTALLINE SILICA.

=====  
===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING/GET MED AT TN. INHALATION:

REMOVE TO FRESH AIRIF BREATHING HAS STOPPED GIVE CPR. GET MED ATTN. EYE: FLUSH W/WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS. GET MED ATTN. SKIN: REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREA. OBTAIN MED ATTN IF IRR'N PERSISTS. TREATMENT REQ FOR OVER-EXPOSURE S/B DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

=====  
===== Fire Fighting Measures =====

Flash Point:59F 15.00C

Extinguishing Media:USE NFPA CLAS

S B FIRE EXTINGUISHERS. POLYMER FOAM

IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER TO COOL CONT TO PREVENT POSSIBLE AUTO-IGNITION OR EXPLOSION. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MED ATTN. WARNING! FLAMMABLE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE/CONTAIN SPILL WITHINERT MAT'L. TRANSFER LIQ'S/ABSORBENT DIKING MAT'LIN COVERED METAL CONT'S FOR RECOVERY/DISPOSAL. USEONLY NON-SPARKING TOOLS. PREVENT CONTAM OF SEWERS/ STREAMS/GROUNDWATER W/SPILLED MAT'L/USED ABSORBENT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA

29CFR1910.106.

Other Precautions:DO NOT BREATHE SANDING DUST OR REUSE EMPTY CONT. DO NOT TAKE INTERN. CONT'ER S/BGROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE OR CUT CONT'R.NEVER USE PRESS TO EMP. CLOSE AFTER EA U SE. DO NOT USE IF REACT TO ISOCYANATES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR (TC 19C NIOSH/MSHA). IF NOT AVAIL-ABLE, USE A VAPOR PARTICULATE, (P

AIN T SPRAY) RESPIRATOR THAT MANUFACTURER RECOM UNTIL ISOCYANATE VAPORS AND MISTS ARE GO NE DURING MIXING OR SPRAYING.

Ventilation:PROVIDE DILUTION/LOCAL EXHAUST VENTILATION TO KEEP CONCEN- TRATIONS OF HAZARDOUS INGRID BELOW EXPOSURE LIMITS STATED.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTA/CHEM SPLASH GOGGLES.

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH WITH SOAP WATER HANDS/FACE THROUGHL Y BEFORE E

ATING OR DRINKING.

Supplemental Safety and Health

NK

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:210F 475F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:48

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF

I  
GNITION.

Hazardous Decomposition Products:BURNING, INCLUD WHEN HEATED BY WELDING/CUTTING, WILL PRODUCESMOKE/CARBON MONOXIDE-DIOXIDE/NITROGEN OXIDES. HYDROGEN GAS.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS AND FLAME.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ONLY IN EPA PERMITTED FACILITY.

DISPOSE ONLY IAW FED/STATE/LOCAL REGS. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DIS-

POSAL OF FLAMMABLE

MAT'S. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.