Address:234 SUYDAM AVENUE Box:B

City: JERSEY CITY

State:NJ ZIP:07304 Country:US

Info Phone Num:201-333-6968

Emergency Phone Num:800-424-9300 (24 HOURS)

CAGE:34094 === Contractor I dentification ===

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306 Country:US

Phone:201-333-6986

CAGE:34094

======= Composition/Information on Ingredients ========

Ingred Name: VM&P NAPHTHA

CAS:64742-89-8 Fraction by Wt: 74% ACGIH TLV:300 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITS WHICH CAN BEFATAL. Effects of Overexposure: EYE: SEVERE IRRIT., RDNESS, TEARING, BLURRED VISION; SKIN: MOD. IRRIT., DEFATTING, SKIN: MOD. IRRIT., DEFATTING, DERMATITIS.; INHAL: NASAL/RESPIRATORY IRRITATION CNTL NERV SYST, DIZZINESS, WEAKNESS, FATIGUE, HDACHE, & UNCONSC., EVEN DEATHINGST: GASTROINTESTINAL IRRIT., NAUSEA, VOMITING, DIARRHEA. Medical Cond Aggravated by Exposure: SKIN C ONTACT MAY AGGRAVATE AN EXISTING DERMATITIS. First Aid:EYE: FLUSH W/LG AMNTS OF WTR, LIFTING EYELIDS OCCASIONALLY, GET MEDICAL ATTENTIONSKIN: WASH EXPOSED AREA WITH SOAP AND WATER INHAL: REMOVE TO FRESH AIR, GIVE ARTIFIC AL RESPIRATION FI NECESSARY, KEEP PERSONWARM/QUIET, GET MEDICAL ATTENTION.; INGST: DO NOT INDUCE VOMITING, KEEP PERSON WARM/QUIET AND GET MEDICAL ATTENTION. _____ === Fire Fighting Measures =========== Flash Point Method:TCC Flash Point:50F/10C Lower Limits:0.9 **Upper Limits:6** Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE OR FOAM. Fire Fighting Procedures: KEEP AWAY FROM SOURCES OF IGNITION. WEAR SELF CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard: ALL LARGE METAL CONTAINERS SHOULD BE GROUNDED/BONDED WHEN MATL IS TRANSFERRED. ======== Accidental Release Measures ============ Spill Release Procedures:EL IMINATE ALL SOURCES OF IGNITION. ABSORB WITH ABSORBENT MATERIAL & SHOVEL/TRANSFER TO CONTAINERS. DIKE AREA OF

SPILL TO PREVENT SPREADING, PUMP LIQ. TO SALVAGE TANK. WEAR PROTECTIVE EQUIPMENT.

============= Handling and Storage ==========================

Handling and Storage Precautions: KEEP AWAY FROM SOURCES OF IGNITION. Other Precautions: PREVENT RUN OFF TO SEWERS, STREAMS OR OTHER BODIES OF BODIES OF WATER. IF RUN OFF OCCURS, NOTIFY PROPER AUTHORITIES AS REQUIRED,

Respiratory Protection:WEAR SELF CONTAINED BREATHING APPARATUS Ventilation:LOCAL EXHAUST OR MECHANICAL VENTILATION Protective Gloves:IMPERVIOUS GLOVES Eye Protection:SAFETY GLASSES Supplemental Safety and Health
NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:240F/116C Vapor Pres:15 Vapor Density:3.8 Spec Gravity:0.727
pH:7.0 Evaporation Rate & Refer ence:1.00
Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR AMBER ALIPHTIC ODOR Percent Volatiles by Volume:75
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR BASES, OXIDIZING AGENTS & SELECTED AMINES Hazardous Decomposition Products:CARBON MONOXIDE/DIOXIDE
======== Disposal Considerations ===========
Waste Disposal Methods:IN ACCORDANCE WITH LOCAL, STATE, OR FEDERA REGULAT IONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular

====== Exposure Controls/Personal Protection ========

THAT A SPILL HAS OCCURRED.

