

PLASTI-KOTE CO., INC. -- ENAMEL AEROSOL SPRAY PAINT RED 11136 -- 8010-00-079-3760

===== Product Identification =====

Product ID:ENAMEL AEROSOL SPRAY PAINT RED 11136

MSDS Date:12/30/1986

FSC:8010

NIIN:00-079-3760

MSDS Number: BHMCR

=== Responsible Party ===

Company Name:PLASTI-KOTE CO., INC.

Address:1000 LAKE ROAD

City:MEDINA

State:OH

ZIP:44256

Country:US

Info Phone Num:(216) 725-4511

Emergency Phone Num:(216) 725-4511

CAGE:HO182

=== Contractor Identification =

==

Company Name:PLASTI-KOTE CO., INC.

CAGE:HO182

Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC

Address:1000 LAKE ROAD

Box:City:MEDINA

State:OH

ZIP:44256

Country:US

Phone:330-725-4511

CAGE:07708

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 30-40%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS

:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 5-10%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)  
CAS:64-17-5  
RTECS #:KQ6300000  
Fraction by Wt: 5-10%  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM; 9192

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)  
CAS:123-42-2  
RTECS #:SA9100000  
Fraction by Wt: 5-6%  
OSHA PEL:50 PPM  
ACGIH TLV:50 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 5%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INTENTIONAL MISUSE BY DELIBERATELY  
CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.  
Effects of Overexposure:INHALING CAN  
CAUSE NASAL & RESPIRATORY  
IRRITATION, DIZZINESS, WEAKNESS, FATIGUE,NAUSEA, HEADACHE, POSSIBLE  
UNCONSCIOUSNESS AND EVEN ASPHYXIATION. EYE CONTACT CAN CAUSE  
SEVERE IRRITATION, REDNESS, TE ARING, BLURRED VISION. SWALLOWING  
CANCAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING,  
DIARRHEA.SKIN IRRITANT.  
Medical Cond Aggravated by Exposure:CAN CAUSE ALLERGIC RESPIRATORY  
AND/OR SKIN REACTION.

===== First Aid Measures =====

First Ai

d:INHALED:REMOVE TO FRESH AIR. GIVE CPR AND OXYGEN IF NECESSARY. SEEK MED. HELP. EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE OCCASSIONALLY HOLDING EYELIDS OPEN. GET MED. ATTN. IF SWALLOWED: DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET, &GET MEDICAL ATTENTION/POISON CONTROL CENTER. IN ON SKIN: WASH WITH SOAP AND WATER OR VARIOUS HAND CLEANERS, AND WASH CLOTHING BEFORE RE-USE.

===== Fire Fighting Measures =====

Flash Point:NR

Lower

Limits:1.0

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL CLOSED CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED. USE S.C.B.A. WITH FULL FACE PIECE.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE AND/OR AUTOIGNITE WHEN EXPOSED TO EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL/BE MOVED BY VENTILATION TO IGNITION SRC

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. VENTILATE AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO A CLOSED CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE IN AREAS ABOVE 120F OR IN DIRECT SUN-LIGHT OR NEAR HEAT OR OPEN FLAMES. DO NOT PUNCTURE OR INCINERATE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR CASUAL/OCCASSIONAL USE-OPEN WINDOWS AND DOORS OR USE OTHER MEANS TO ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. IF OVEREXPOSURE SYMPTOMS OCCUR, WEAR NIOSH/MSHA RESPIRATORY PROTECTION OR LEAVE THE AREA.

Ventilation:FOR REGULAR/CONTINUOUS USE-PROVIDE SUFFICIENT MECHANICAL AND/OR LOCAL EXHAUST VENTILATION.

Protective Gloves:CHEMICAL RESISTANT GLOVES/NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Work Hygienic Practices

:WASH HANDS BEFORE EATING OR USING WASHROOM. AS  
WITH ALL CHEMICALS, MINIMIZE PERSONAL CONTACT AND BREATHING OF  
VAPORS

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:133 - 331F

Melt/Freeze Pt:M.P/F.P Text:MIN. 1500F

Vapor Density:> AIR

Spec Gravity:< 1

Evaporation Rate & Reference:SECT.1 PROD.>1/PROPELNT