View NSN Online: https://aerobasegroup.es/nsn/8010-00-281-2074

Product ID:TT-S-711C LIGHT WALNUT

MSDS Date:03/01/1989

FSC:8010

NIIN:00-281-2074

MSDS Number: BHMJF === Responsible Party ===

Company Name: ASAHIPEN AMERICAN INC.

Address:1126 SW SPOKANE STREET

City:SEATTLE State:WA

ZIP:98134-1197 Country:US

Info Phone Num:206-682-4603 Emergency Phone Num:303-573

-1014 POISON CENTER

Preparer's Name: DOUGLAS KIER

CAGE:DO047

=== Contractor Identification ===

Company Name: ASAHIPEN AMERICA INC.

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134-1197

Phone:303-573-1014 POISON CENTER

CAGE:DO047

====== Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS

(VAPOR PRESSURE 2.0 MM HG @ 68 F)

CAS:64475-85-0 RTECS #:PY8240000 OSHA PEL:500 PPM ACGIH TLV:100 PPM

Ingred Name: MINERAL SPIRITS

CAS:68551-16-

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NOTICE: REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL OVER-EXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL

OR FATAL.

Explanation of Carcinogenicity:

NO

Effects of Overexposure:INHALE: NASAL & RESPIRATORY IRRI, DIZZI, WEAK, FATIGUE, NAUSEA, HEADACHE, POSS- IBLE UNCONSC & EVEN ASPHYXIATION. SKIN: MOD IRRI, DEFATT, DERMATITIS. EYE: RED, IRRI, TEARING, BLURRED VISION. SWALLOW: GASTRONINTESTINAL IRRI, NAUSEA, VOMITINGDIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE CHEM PNEUMONITIS WHICH CAN BE FATAL.

First Aid:INHALE: REMOVE TO FRESH AIR. IF BREATH IS DIFFICULT, ADMIN

OXYGEN. IF BREATH HASSTOPPED GIVE CPR. KEEP PERSON WARM, QUIET & GET MED ATTN. EYE: WASH WITH WATER 15 MIN. CONSULT PHYSICIAN. SKIN: IF IRRI PERSISTS, WASH THOROUGHLY WITH SOAP &WATER, REMOVE & WASH CLOTHING BEFORE RE-USE. INGEST: DO NOT INDUCE VOMIT. GET MED ATTN. ASPIRATION INTO LUNGS CAN CAUSE CHEM PNEUMONITIS WHICH CAN BE FATAL.

Flash Point Method:TCC Flash Point:103 F/ 39 C

Lower Limits:

1.0

Extinguishing Media:USE FOAM, CO2, DRY CHEMICAL, WATER SPRAY OR FOG Fire Fighting Procedures:CLOSED CONTAIN MAY EXPLODE FROM EXTREME HEAT. USE WATER FOR COOLING PURPOSES. AVOID SPREADING OF BURNING LIQUID. SELF-CONTAINED BREATHING APPARATUS IS NEEDED.

Unusual Fire/Explosion Hazard:DON'T APPLY TO HOT SURFACES. KEEP AWAY FROM HEAT, SPARK, ELEC EQUIP & OPEN FLAMEDO NOT STORE OR MIX WITH STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

======= Accidental Release Me

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. KEEP PEOPLE AWAY. RE-COVER FREE LIQ. ADD ABSORBENT (SAND, EARTH, ETC.) TO SPILL AREA. AVOID BREATHING VAPORS. VENT AREA. KEEP OUT OF SEWERS & WATERCOURSES BY DIKING OR IM- POUND. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

========== Handling and Storage ===============

Handling and Storage Precautions:DON'T HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANT. ADEQUAT

E VENTILATION REQUIRED. NO

SMOKING OR OPEN LIGHTS. DON'T TAKE INTERNALLY.

Other Precautions:REMOVE CONTAMINATED CLOTHING, LAUNDER BEFORE REUSE. WASH SKIN THOROUGHLY WITH SOAP & WATER AFTER CONTACT. GROUND CONTAINERS WHEN POURING & LIMIT FREE FALL TO MINIMIZE STATIC CHARGE BUILD-UP. EMPTY C ONTAINERS MAY BE HAZARDOUS FROM RESIDUE.

===== Exposure Controls/Personal Protection ========

Respiratory Protection: USE ORGANIC VAPOR CANISTER OR SUPPLIED-AIR RESPIRATORY

PROTECTION WHEN TLV IS EXCEEDED.

Ventilation:APPLICATION AREAS-PROVIDED WITH SUFFICIENT MECH VENTILATION W/EXPLOSION PROOF EQUIP TO MAINTAIN EXPOSURE LEVEL BELOW TLV

Protective Gloves: SOLVENT RESISTANT GLOVES

Eye Protection: SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:PROTECTIVE CREAM WHERE SKIN CONTACT IS LIKELY. WEAR IMPER- VIOUS CLOTHING & BOOTS TO PREVENT REPEATED/PROLONGED CONTACT

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING THE WASHROOM, SMOKE IN

SMOKING AREAS ONLY.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT WITH SKIN OR BREATHING OF SPRAY MIST. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN. THIS PRODUCT CON-TAINS NO LEAD PIGMENT. EMPTY CONTAINERS MAY BE HAZARDOUS FROM RESIDUES/VAPORS &ALL CAUTIONS ON THIS SHEET APPLY TO THEM.

======== Physical/Chemical Properties ==========

Boiling Pt:B.P. Text:314-383 F Vapor Density:> AIR Viscosity:10"-25" 4FC Evapora tion Rate & Deference: SLOWER THAN ETHER
Solubility in Water: NEGLIGIBLE
Appearance and Odor: THIN LIQUID, VARIOUS COLORS, MILD ODOR
Percent Volatiles by Volume: 65-69

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HIGH TEMPERATURE OR DIRECT HEATING
Hazardous Decomposition Products:MAY PRODUCE FUMES WHEN HEATED TO
DECOMP. FUMES MAY CONTAIN CARBON MONOXIDE
/DIOXIDE, VARIOUS
HYDROCARBONS, ETC.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS. BEFORE ATTEMPTING CLEAN-UP, REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.