

PRATT AND LAMBERT INC -- ENAMEL ALKYD LUST BLACK 37038 ID 741702 -- 8010-00-297-0546  
===== Product Identification =====

Product ID:ENAMEL ALKYD LUST BLACK 37038 ID 741702

MSDS Date:06/05/1989

FSC:8010

NIIN:00-297-0546

MSDS Number: BHMKV

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-136

1

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

(VP 2 MM HG @ 20 DEG.C)

CAS:64475-85-0

RTECS #:PY8240000

OSHA PEL:500 PPM 2950 MG/CU.M

ACGIH TLV:100 PPM 525 MG/CU.M.

Ingred Name:S

SILICA, CRYSTALLINE - QUARTZ  
CAS:14808-60-7  
RTECS #:VV7330000  
OSHA PEL:SEE TABLE Z3  
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE  
CAS:14464-46-1  
RTECS #:VV7325000  
OSHA PEL:SEE TABLE Z3  
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN  
1% CRYSTALLINE SILICA  
CAS:61790-53-2  
RTECS #:HL8600000  
OSHA PEL:20 MPPCF  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)  
CAS:14807-96-6  
RTECS #:WW271  
0000  
OSHA PEL:2 MG/M3 RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:PROPYLENE GLYCOL METHYL ETHER ACETATE  
(VP 2 MM HG @ 20 DEG.C)  
CAS:108-65-6  
RTECS #:AI8925000  
OSHA PEL:NONE ESTABLISHED  
ACGIH TLV:NONE ESTABLISHED

Ingred Name:VOC. ORGANIC CMPD 3.83 LB/GL LESS WATER & NPRS\* 460 G/L  
LESSWATER VOC 9.07 LB/GAL SOLIDS 1088 G/L SOLIDS CALCULATED.  
RTECS #:9999999VO

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Inge

stion:YES

Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SWALLOWING: CAN CAUSE GASTROINTESTINAL IRR/NAUSEA/VOMIT. ASPIRATION OF MAT'L MAYCAUSE CHEM PNEUMONITIS. INHALATION: NOSE/THROAT IRRITA. HIGH CONCENTRATION MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION CHAR BY HEADACHES/DIZZINESS/NAUSEA/CONFUSION. EYE: MAY CAUSE EYE IRRITA. SKIN: MAY CAUSE SEVERE SKIN IRRITATION.

Explanation of Carcinogenicity:THE IARC CONSIDERS CRYSTALLINE SILICA TO

HAVE LIMITED EVIDENCE OF CARCINOGENICITY IN HUMANS.

Effects of Overexposure:REPEATED EXPOSURE TO CRYSTALLINE SILICA MAY CAUSE PNEUMOCONIOSIS. REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAG E. INTENTIONAL MISUSE BY DELIBERATELYCONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:PREEXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO CRYSTALLINE SILICA.

===== First Aid Measures =====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING/GET MED ATTN. INHALATION: REMOVE TO FRESH AIRIF BREATHING HAS STOPPED GIVE CPR. GET MED ATTN. EYE: FLUSH W/WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS. GET MED ATTN. SKIN: REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREA. OBTAIN MED ATTN IF IRR'N PERSISTS. TREATMENT REQ FOR OVER-EXPOSURE S/B DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS.

===== Fire Fighting Measures =====

Flash Point:>102F 38.89C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER TO COOL CONT TO PREVENT POSSIBLE AUTO-IGNITION OR EXPLOSION. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT/ELEC EQUIP/SP

ARKS/FLAME. CONT MAY EXPLODE WHEN EXPOSED TO HEAT.  
OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZ. OBTAIN MED  
ATTN.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE/CONTAIN SPILL  
WITHINERT MAT'L. TRANSFER LIQ'S/ABSORBENT DIKING MAT'L IN COVERED  
METAL CONT'S FOR RECOVERY/DISPOSAL. USE ONLY NON-SPARKING TOOLS.  
PREVENT CONTAM OF SEWERS/ STREAMS/GROUNDWATER W/SPILLED MAT'L/USED  
ABSORBENT

==  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F. STORE  
LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.  
Other Precautions:DO NOT BREATHE SANDING DUST OR REUSE EMPTY CONT. DO  
NOT TAKE INTERN. CONT'R S/BGROUNDED AND BONDED TO THE RECEIVING  
CONTAINER. DO NOT WELD/BRAZE OR CUT CONT'R.NEVER USE PRESSURE TO  
EMPTY. DRUM IS NOT A PRESSURE VESSEL. CLOSE AFTER EA USE.

===== Exposure C  
ontrols/Personal Protection =====

Respiratory Protection:WELL VENTILATED AREA-RESP NOT REQ. RESTRICTED  
VENT-NIOSH CHEMICAL CARTRIDGE MAY BE REQ. IF SPRAYING, MECH  
PREFILTER MAY BE REQ. IF TLV ARE EXCEEDED, USE A PROP FITTED  
NIOSH/MSHA RESP W/APPROP PROTECTI ON FACTOR. SEE OSHA 29 CFR  
1910.134.  
Ventilation:PROVIDE DILUTION/LOCAL EXHAUST VENTILATION TO KEEP  
CONCENTRAOF HAZARDOUS SUBSTANCES BELOW EXPOSURE LIMITS STATED.  
Protective Gloves:SOLVENT IMPERMEABLE GLOVES.  
Eye  
Protection:WEAR SAFETY SPECTACLES.  
Other Protective Equipment:NOT LIKELY TO BE NEEDED.  
Work Hygienic Practices:WASH WITH SOAP AND WATER HANDS/FACE THOROUGHLY  
BEFORE EATING OR DRINKING.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:280F 388F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER.  
Percent Volatiles by Volume:57

===== Stability and Reactivity Data =====

==

Stability Indicator/Materials to Avoid: YES  
STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT AND SOURCES OF  
IGNITION.

Hazardous Decomposition Products: BURNING, INCLUDING WHEN HEATED BY  
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON  
DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND  
FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE ONLY  
IN EPA PERMITTED FACILITY.

DISPOSE ONLY IAW FED/STATE/LOCAL REGS. DO NOT INCINERATE CLOSED  
CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE  
MATS. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARDOUS  
WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.