

PRATT AND LAMBERT INC -- LACQUER ACRYLIC YELLOW 13538, ID794310 -- 8010-00-935-7067
===== Product Identification =====

Product ID:LACQUER ACRYLIC YELLOW 13538, ID794310

MSDS Date:10/14/1988

FSC:8010

NIIN:00-935-7067

MSDS Number: BHMYV

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W.A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2

;8990

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:T

OLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:LEAK MOLYBDATE

CAS:10190-55-3

OSHA PEL:.0500 MG/CU.M.

ACGIH TLV:.1500 MG/CU.M.

Ingred Name:VOC. ORGANIC CMPD 5.0 LB/GAL LESS WATER & NPRS* 600 G/L

LESS WATER VOC. 16.2 LB/GAL SOLIDS 1944 G/L SOLIDS CALCU

RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES I

ngestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:REPEAT/PROLONGED OVEREXP TO RELATIVELY INSOLUBLE CHROMATES-LUNG CANCER. TOLUENE-LIVER DAM. CHRONIC OVEREXP TO LEAD-SEVERE DAMAGE TO BLOOD FORMING, NERV, URINARY& REPROD SYS. CHAR: LOSS APPETITE, METAL LIC TASTE, ANXIETY, CONSITP, NAUSEA, WEAK, INSOMNIA, HEADACHE, MUSCLE & JOINT PAIN, FINE TREMORS, NUMBNESS, DIZZ, HYPER

Explanation of Carcinogenicity:IN LAB ANIMALS: KIDNEY, LUNG & SPLEEN DAMAGE.

Effects of Overexposure:SWALLOW: GASTROINTESTINAL IRRI, NAUSEA, VOMIT, ASPIRATION INTO LUNG, CHEM PNEUMONITITS, CAN BE FATAL. INHAL: NOSE/THROAT IRRI. HIGH CONCENT CAUSE ACUTE CENT NERV SYS DEPRESSION CHAR HEADACHE, DIZZ, NA USEA & CONFUSION. EYE: IRRI. SKIN: DEFATTNG AND IRRITATION OF THE SKIN. INHAL OF CAN CAUSE ASPHYXIATION OR ANESTHETIC.

Medical Cond Aggravated by Exposure:PREEXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO LEAD. PROLONGED/REPEATED OCCUP OVEREXP TO SOLVENTS WITH PERMANENT BRAIN & NERV SYS DAMAGE. MISUSE MAY BE HARMFUL AND/OR FATAL

=====
===== First Aid Measures =====

First Aid:SWALLOW: DO NOT INDUCE VOMIT. CALL POISON CONTROL CENTER/HOSPITAL EMERG ROOM/PHYSICIAN IMMED. INHAL: REMOVE TO FRESH AIR IMMED. BREATH HAS STOPPED, GIVE CPR. KEEP WARM, QUIET. GET MED ATTN IMMED. EYE: FLUSH W/LARGE AMTS OF WATER, LIFTING LIDS OCCAS, FOR AT LEAST 15 MIN. GET MED ATTN. SKIN: REMOVE CONTAM CLOTHES. WASH AFFECT AREA W/SOAP & WTR. OBTAIN MED ATTN. IRRI PERSISTS.

=====
===== Fire Fighting Measures =====

Flash Point:24 F/-4.44 C

Extinguishing Media:NFPA CL B FIRE EXTING (CARBON DIOXIDE, ALL PUR DRY CHEM OR ALCOHOL FOAM) FOR EXTING FLAMM LIQ FIRES. POLYMER FOAM PERFER

Fire Fighting Procedures:SELF CONTAIN BREATH APPARATUS. WTR MAY BE INEFFECT, USED TO COOL TO PREVENT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION F

ROM HEAT. IF WTR USED, FOG NOZZLES

PREFERR

Unusual Fire/Explosion Hazard:EMERG COND, OVEREXP TO DECOMP MAY CAUSE HEALTH HAZARD. SYMP MAY NOT BE IMMED APPARENT. OBTAIN MED ATTN. WARNING! FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM ALL IGNITE SOURCES. DIKE & CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQ TO COVER METAL CONTAIN FOR RECOVERY/DISPOSAL. USE NON-SPARK TOOS. PREVENT CONTAM OF SE WERS, STREAMS & GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORB

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEG F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106 DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT BREATHE SANDING DUST. WASH HANDS & FACE THOROUGHLY BEFORE EATING/DRINKING. EMPTY CONT MUST NOT BE WASHED & RE-USED F OR ANY PURPOSE. CONT GROUNDED/BONDED TO RECEIVING CO NT. DO NOT WELD/BRAZE/CUT EMPTY CONT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:GEN EXP TO ORGANIC CHEM MAY NOT REQUIRE RESPIR PROTECT IF WELL VENT AREA. RESTRICTED VENT AREA NIOSH APPROVED CHEM CARTRIDGE RESPIR MAY BE REQUIRED. SPRAYNG: MECH PREFILTER MAY ALSO BE REQUIRED. CONFI NED: NIOSH APPR AIR SUPPLIED RESPIRATOR

Ventilation:GEN DILUTION & LOCAL EXHAUST VENT SUFFICIENT VO L/PATTERN

KEEP CONCEN HAZARD INGRED BELOW THE LOWEST EXPOSURE LIMIT

Protective Gloves:PROLONGED USE, SOLVENT IMPERMEABLE GLOVE

Eye Protection:SAFETY GLASSES/CHEM GOGGLES/FACE SHIELDS

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT. NOT LIKELY TO BE NEEDEDSEE OSHA STANDARD FOR LEAD.

Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES

Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED A HAZARDOUS WASTE BASEDON ITS IGNITABILITY CHA

R. THIS PRODUCT CONTAINS LEAD,
WHICH, IF PRESENT IN WASTE AT 5.0 MG/L OR MORE AFTER BEING EXTRACTED,
IS CONSIDERED EP TOXIC, AND THEREFORE A HAZARDOUS WASTE UNDER
RCRA REGULATIONS. HAZARD WASTE NO. D008

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-232 F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid:YES

AVOID EXCESSIVE HEAT & SOURCES OF IGNITION. STRONG ACIDS OR ALKALINE
MATERIALS

Stability Condition to Avoid:NORMALLY STABLE

Hazardous Decomposition Products:BURNING, INCLUDE WHEN HEATED BY
WELD/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE.
OXIDES OF LEAD-GENERAL

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT SPARKS AND FLAME

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE

OF ACCORD FED, STATE & LOCAL LAWS. INCIN

ONLY EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONT. OBSERVE
PRECAUTIONS FOR FLAMM DISPOSAL. CONTAM ABSORB DISPOSE IN HAZARDOUS
WASTE LANDFILL. IN ACCORD W/FED, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this in

formation to be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.