Product ID:CASCOSET FM 124 D MSDS Date:12/13/1989 FSC:8040 NIIN:00-054-5023 Kit Part:Y **MSDS Number: BHQGM** === Responsible Party === Company Name: CONSUMER PRODUCTS DIV., DIV. OF BORDEN, INC. Address:180 EAST BROAD STREET City:COLUMBUS State:OH ZIP:43215 Country:US Info Phone Num:614-431-6680 Emergency Phone Num:614-431-6600 CAGE:DO149 === Con tractor Identification === **Company Name:BORDEN INC** Address:180 E BROAD ST Box:208 City:COLUMBUS State:OH ZIP:43215-3705 Country:US Phone:614-225-6124 CAGE:07982 Company Name: CHEMICAL COMMODITIES AGENCY, INC. Address:27447 PACIFIC STREET Box:City:HIGHLAND State:CA ZIP:92346-2640 Country:US Phone:909-864-2310 CAGE:60777 Company Name: CONSUMER PRODUCTS DIV., BORDEN INC. Address:180 EAST BROAD STREET City:COLUMBUS State:OH ZIP:43215 Phone:614-431-6600 CAGE:DO149

======= Composition/Informatio

n on Ingredients =========

Ingred Name:FORMALDEHYDE (SARA III) CAS:50-00-0 RTECS #:LP8925000 OSHA PEL:SEE 1910.1048 ACGIH TLV:C 0.3 PPM; A2; 9293 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:PARAFORMALDEHYDE (SARA III) CAS:30525-89-4 RTECS #:RV0540000 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

INHALATION: HARMFUL

Ingred Name:SOFTWOOD FLOUR (DUST 5 MG/M3 TWA; 10 MG/M3 STEL) (WOOD DUST 5 MG/M3 TWA)

Ingred Name:WOOD, HARD, FLOUR (WOOD DUST 1 MG/M3 TWA) (DUST 5 MG/M3 TWA; 10 MG/M3 STEL)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ALLERGIC SKIN REACTION. MAY CAUSE
ASTHMA. CAN CAUSE LUNG DAMAGE, RESPIRATORY DISORDERS MAY BE
AGGRAVATED. MAY CAUSE
ALLERGIC RESPIRATORY & SKIN REACTIONS. OSHA
STATED THAT A CONCENTRATION OF 100 PPM I S IMMEDIATELY DANGEROUS TO
LIFE & HEALTH
Explanation of Carcinogenicity:AS OF THE DATE OF ISSUANCE OF THIS
DOCUMENT, THIS MATERIAL HAS NOT BEEN LISTED AS A CARCINOGEN.
Effects of Overexposure:SKIN ABSORPTION: MAY BE HARMFUL. INGESTION: NOT
EXPECTED HARMFUL UNDER NORMAL CONDITIONS. SWALLOWED: BURNS OR
IRRITATION TO MUCOUS MEMBRANES, ESOPHAGUS OR GI TRACT CAN RESULT.

IF INHALED. CAN BURN NOSE, THROAT &
LUNGS.SKIN: CAUSES IRRITATION AND EYES: CAUSES BURNS.
Medical Cond Aggravated by Exposure: PRE-EXISTING RESPIRATORY AND SKIN
DISORDERS MAY BEAGGRAVATED BY EXPOSURE.

First Aid:IMMEDIATELY FLUSH EYES OR SKIN WITH PLENTY OF WATER AT LEAST 15 MINUTES, REMOVE CONTAMINATED CLOTHES & SHOES. LAUNDER CLOTHES BEFORE REUSE. INGESTION: DILUTE BYDRINKING LARGE AMTS OF WATER. IMMEDIA

TEL Y CONTACT POISON CONTROL CENTER/HOSPITALFOR ADD TREATMENT DIRECTIONS. INHALE: REMOVE TO FRESH AIR, CPR/OXYGEN IF NEEDED.CALL PHYSICIAN. EYELIDS SHOULD BE HELD APART TO INSURE WATER CONTACT TO THE EYES

Flash Point:160 F/ 71 C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:USE DRY CHEMICAL, ALCOHOL FOAM OR CO2; WATER MAY BE INEFFEC-TIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINER COOL
Fire Fi
ghting Procedures:COMBUSTIBLE. KEEP AWAY FROM HEAT AND FLAME.
USE DRY CHEMICAL, ALCOHOL FOAM OR CO2; WATER MAY BE INEFFECTIVE, BUT USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. SWEEP (SCOOP) UP & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Handling and St

orage Precautions:LIMITED STORAGE LIFE, REFER TO PRODUCT SPECIFICA- TIONS. AVOID CONTACT WITH EYES OR SKIN, ALSO AVOIDBREATHING. USE WITH ADEQUATE VENTILATION. Other Precautions:HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE & SAFETY PRACTICES. IF AIR- BORNE CONTAMINANTS ARE GENERATED WHEN MATERIAL IS HEATED/HANDLED, SUFFICIENT VENT IN VOL/PATTERN SHOULD BE PROVIDED T O KEEP AIR CONTAM CONCENTRATE ACCEPTABLE

======= Exposure Controls/Personal Protection =======

Respiratory Protection: WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA, USE NIOSH/MSHA APPROVED FULL FACEPIECE RESPIRATORY PROTECTION EQUIPMENT. RESPIRATORS SHOULD BE SELECTED BASED ON FORM & CONCENTRATE OF CONTAM IN AIR IN ACCORDANCE W/OSHA STANDARDS/REG. Ventilation: LOCAL EXHAUST VENTILATION ENCLOSED SYSTEM DESIGN, PROCESS **ISOLATION & REMOTE CONTROL COMB W/APPROPRIATE PERSON PROTECT** Protective Gloves: IMPERVIOUS GLOVES AS REQUIRED. Eye Protection: CHEMICAL SPLASH **GOGGLES OR OTHER TYPE** Other Protective Equipment: EYE WASH FOUNTAIN, SAFETY SHOWER, REUSABLE PROTECTIVE CLOTH-ING SHOULD BE CLEANED & VENTILATED AFTER FORMALDEHYDE CONTAM Work Hygienic Practices: GOOD PERSONAL HYGIENE. LAUNDER CLOTHING BEFORE RE-USE. Supplemental Safety and Health PROTECTIVE EQUIPMENT AND CLOTHING AND OSHA 29CFR 1910.1048(I) HYGIENE PROTECTIONFOR OTHER SPECIFIC REQUIREMENTS BASED ON THE FORM OF FORMALDEHYDE, THE CONDITIONOF USE AND THE HAZARDS TO BE PREVENTED. Appearance and Odor: DRY POWDER, TAN/BROWN IN COLOR, WITH DISTINCT FORMALDEHYDE ODOR. Stability Indicator/Materials to Avoid:YES REACTS W/MANY COMPOUNDS/RHENOL/STRONG ACIDS/ALKALIS MAY BE VIOLENT. REACTION W/HYDROCHLRIC ACID-FORMS BIS-CHLOROMETHYL Stability Condition to Avoid: MAY BECOME UNSTABLE AT HIGH TEMP OR MAY REACT W/WATER. TREATAS A COMB **USTIBLE DUST IN FINELY DIVIDED &** SUSPENDED STATE. Hazardous Decomposition Products:CO, CO2, ELDEHYDES (INCLUDES FORMALDEHYDE), HYDROGEN CYANIDERARTICULATE MATTER AND OTHER ORGANIC COMPOUNDS.

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE/PROVINCIA, & FED REQ. EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VA-PORS, DON'T CUT, PUNCTURE OR WELD ON/NEAR. KEEP CONTAINER CLOSED. STORE IN A COOL, DRY PLA

CE. IF EXPOSURE TO MOISTURE-LUMPS, BREAK-UP INTO POWDER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.