

INDUSTRIAL FLOOR FINISHES -- METAL POLISH -- 7930-00-266-7136

===== Product Identification =====

Product ID:METAL POLISH

MSDS Date:05/01/1987

FSC:7930

NIIN:00-266-7136

MSDS Number: BHQJD

=== Responsible Party ===

Company Name:INDUSTRIAL FLOOR FINISHES

Address:605 SPRINGS RD

City:BEDFORD

State:MA

ZIP:01730

Country:US

Info Phone Num:1-617-667-5161

Emergency Phone Num:1-800-424-9300

Preparer's Name:T. PITROLFFY

CAGE:INDUS

=== Contractor Identification ===

Company

Name:INDUSTRIAL FLOOR FINISHES

Address:605 SPRINGS RD

City:BEDFORD

State:MA

ZIP:01730

Country:US

Phone:1-617-667-5161

CAGE:INDUS

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 17%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:PRIMARY EYE/SKIN

IRRITANT WITH  
CONTACT. INHALATION MAY CAUSE HEADACHE, DIZZINESS AND NAUSEA.  
CHRONIC: NOT SUFFICIENT DATA, EXERCISE CARE, DO NOT USE ABOVE TLV.  
Effects of Overexposure: PRIMARY EYE/SKIN IRRITANT WITH CONTACT.  
INHALATION MAY CAUSE HEADACHE, DIZZINESS AND NAUSEA.

===== First Aid Measures =====

First Aid: EYE: FLUSH WITH WATER; SKIN: WASH WITH SOAP AND WATER, APPLY SKIN CREAM. INHAL: REMOVE TO FRESH AIR, RESTORE BREATHING IF NECESSARY  
CALL A PHYSICIAN. INGEST: DRINK WATER OR MILK, DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method: TCC  
Flash Point: 104F/40C  
Lower Limits: 0.8  
Upper Limits: 6  
Extinguishing Media: FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures: WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD-UP OR AUTO-IGNITION.  
Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, CLOSED CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT.

=  
===== Accidental Release Measures =====

Spill Release Procedures: REMOVE SOURCES OF IGNITION, SPRINKLE W/ABSORBENT. FOG WITH WATER FLUSH OR SCRAPE INTO RETAINING AREA OR CONTAINER. INCREASE VENTILATION AVOID BREATHING VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE ADEQUATE VENTILATION. AVOID PROLONGED/REPEATED CONTACT. KEEP CONTAINER CLOSED.  
Other Precautions: KEEP AWAY FROM CHILDREN. AVOID STATIC BUILD UP. EMPTY CONTAINERS MAY RETAIN FUME

===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV  
Ventilation: LOCAL EXHAUST  
Protective Gloves: RUBBER GLOVES  
Eye Protection: SAFETY GLASSES  
Other Protective Equipment: EYE BATH, SAFETY SHOWER, PROTECTIVE CREAM  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

es =====

Boiling Pt:B.P. Text:215F

Vapor Pres:2

Vapor Density:3.8

Spec Gravity:1.1

Evaporation Rate & Reference:0.8

Solubility in Water:PARTIAL

Appearance and Odor:PINK CREAMY LIQUID, AMMONIA ODOR

Percent Volatiles by Volume:74

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, AND FIRE

Hazardous Decomposition Products:THERMAL DECOMP PRODUCES FU

MES MAY

YIELD CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF IN ACCORDANCE

W/FEDERAL, STATE, AND LOCAL REGULATIONS. EMPTY CONTAINERS MAY RETAIN

FUMES. DO NOT EXPOSE TO HEAT OR FLAME.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
express

ly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.